



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 07/01/2019

1 Identification

- **Product identifier**
- **Trade name: H777 2K RMC HARDENER SLOW**
- **Article number: H777**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
General Paint Co. S.A.L.
P.O. Box 7623
Beirut
LEBANON
info@generalpaint.biz
- **Information department: Product Safety Department**
- **Emergency telephone number: 1-800-535-5053 contract number (89244)**

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Warning

- **Hazard-determining components of labeling:**

Homopolymer of hexamethylene diisocyanate

(Contd. on page 2)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 07/01/2019

Trade name: H777 2K RMC HARDENER SLOW

(Contd. of page 1)

xylene

· Hazard statements

Flammable liquid and vapor.
Harmful in contact with skin or if inhaled.
Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Call a poison center/doctor if you feel unwell.
Specific treatment (see on this label).
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
In case of fire: Use for extinction: CO₂, powder or water spray.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:**· NFPA ratings (scale 0 - 4)**

Health = 2
Fire = 3
Reactivity = 0

· HMIS-ratings (scale 0 - 4)

Health = 2
Fire = 3
Reactivity = 0

· Other hazards**· Results of PBT and vPvB assessment****· PBT:** Not applicable.

(Contd. on page 3)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 07/01/2019

Trade name: H777 2K RMC HARDENER SLOW· **vPvB:** Not applicable.

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

1330-20-7	xylene	>25-≤50%
28182-81-2	Homopolymer of hexamethylene diisocyanate	>25-≤50%
108-65-6	2-methoxy-1-methylethyl acetate	>10-≤25%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
 - **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
 - **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.

(Contd. on page 4)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 07/01/2019

Trade name: H777 2K RMC HARDENER SLOW

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

1330-20-7	xylene	130 ppm
28182-81-2	Homopolymer of hexamethylene diisocyanate	7.8 mg/m ³
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
822-06-0	hexamethylene-di-isocyanate	0.018 ppm

- **PAC-2:**

1330-20-7	xylene	920* ppm
28182-81-2	Homopolymer of hexamethylene diisocyanate	86 mg/m ³
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
822-06-0	hexamethylene-di-isocyanate	0.2 ppm

- **PAC-3:**

1330-20-7	xylene	2500* ppm
28182-81-2	Homopolymer of hexamethylene diisocyanate	510 mg/m ³
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
822-06-0	hexamethylene-di-isocyanate	3 ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.

(Contd. on page 5)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 07/01/2019

Trade name: H777 2K RMC HARDENER SLOW

(Contd. of page 4)

Protect against electrostatic charges.

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

1330-20-7 xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

108-65-6 2-methoxy-1-methylethyl acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

- **Ingredients with biological limit values:**

1330-20-7 xylene

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

(Contd. on page 6)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 07/01/2019

Trade name: H777 2K RMC HARDENER SLOW

(Contd. of page 5)

- **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Liquid

Color: Clear

- **Odor:** Characteristic

- **Odor threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 137 °C (278.6 °F)

- **Flash point:** 25 °C (77 °F)

(Contd. on page 7)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 07/01/2019

Trade name: H777 2K RMC HARDENER SLOW

(Contd. of page 6)

· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	315 °C (599 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	10.8 Vol %
· Vapor pressure at 20 °C (68 °F):	6.7 hPa (5 mm Hg)
· Density at 20 °C (68 °F):	0.985 g/cm ³ (8.21983 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	63.0 %
Coating VOC content:	62.96 %
Material VOC content:	620.2 g/l / 5.18 lb/gal
Solids content:	36.9 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.

(Contd. on page 8)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 07/01/2019

Trade name: H777 2K RMC HARDENER SLOW

(Contd. of page 7)

- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

1330-20-7 xylene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
-----------	--------	---

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 9)



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 07/01/2019

Trade name: H777 2K RMC HARDENER SLOW



(Contd. of page 8)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|--|---|
| <ul style="list-style-type: none"> · UN-Number · DOT, ADR, IMDG, IATA | <p style="text-align: right;">UN1263</p> |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT · ADR · IMDG, IATA | <p style="text-align: right;">Paint
1263 PAINT
PAINT</p> |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT | <div style="text-align: right; margin-top: 10px;">  </div> |
| <ul style="list-style-type: none"> · Class · Label | <p style="text-align: right;">3 Flammable liquids
3</p> |
| <ul style="list-style-type: none"> · ADR, IMDG, IATA | |
| <div style="text-align: right; margin-top: 10px;">  </div> <ul style="list-style-type: none"> · Class · Label | <p style="text-align: right;">3 Flammable liquids
3</p> |
| <ul style="list-style-type: none"> · Packing group · DOT, ADR, IMDG, IATA | <p style="text-align: right;">III</p> |

(Contd. on page 10)



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 07/01/2019

Trade name: H777 2K RMC HARDENER SLOW

(Contd. of page 9)

· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	30
· EMS Number:	F-E, S-E
· Stowage Category	A
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· ADR	
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7 xylene

822-06-0 hexamethylene-di-isocyanate

· **TSCA (Toxic Substances Control Act):**

1330-20-7 xylene

ACTIVE

28182-81-2 Homopolymer of hexamethylene diisocyanate

ACTIVE

108-65-6 2-methoxy-1-methylethyl acetate

ACTIVE

822-06-0 hexamethylene-di-isocyanate

ACTIVE

(Contd. on page 11)



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 07/01/2019

Trade name: H777 2K RMC HARDENER SLOW

(Contd. of page 10)

4083-64-1	4-isocyanatosulphonyltoluene	ACTIVE
-----------	------------------------------	--------

· **Hazardous Air Pollutants**

1330-20-7	xylene
822-06-0	hexamethylene-di-isocyanate

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
-----------	--------	---

· **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7	xylene	A4
-----------	--------	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Warning

· **Hazard-determining components of labeling:**

Homopolymer of hexamethylene diisocyanate
xylene

· **Hazard statements**

Flammable liquid and vapor.
Harmful in contact with skin or if inhaled.
Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.

(Contd. on page 12)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 07/01/2019

Trade name: H777 2K RMC HARDENER SLOW

(Contd. of page 11)

Precautionary statements

- Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 - Ground/bond container and receiving equipment.
 - Use explosion-proof electrical/ventilating/lighting/equipment.
 - Use only non-sparking tools.
 - Take precautionary measures against static discharge.
 - Avoid breathing dust/fume/gas/mist/vapors/spray
 - Wash thoroughly after handling.
 - Use only outdoors or in a well-ventilated area.
 - Wear protective gloves/protective clothing/eye protection/face protection.
 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - Call a poison center/doctor if you feel unwell.
 - Specific treatment (see on this label).
 - Take off contaminated clothing and wash it before reuse.
 - If skin irritation occurs: Get medical advice/attention.
 - If eye irritation persists: Get medical advice/attention.
 - In case of fire: Use for extinction: CO₂, powder or water spray.
 - Store in a well-ventilated place. Keep container tightly closed.
 - Store in a well-ventilated place. Keep cool.
 - Store locked up.
 - Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Product safety department
- **Contact:** N/A
- **Date of preparation / last revision** 09/11/2019 / -
- **Abbreviations and acronyms:**
 - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 - ICAO: International Civil Aviation Organisation
 - ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association
 - ACGIH: American Conference of Governmental Industrial Hygienists
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - NFPA: National Fire Protection Association (USA)
 - HMS: Hazardous Materials Identification System (USA)
 - VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 13)

US



Safety Data Sheet
acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 07/01/2019

Trade name: H777 2K RMC HARDENER SLOW

(Contd. of page 12)

LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

US