



800TS 1K Tintable Sealer

Description:


800TS is a 1K tintable automotive sealer with a velvet smooth finish, 800TS is part of the GenRock mixing system making it totally compatible with the GenRock basecoat tints. 800TS has no sensitive recoat issues. 800TS dries quickly, helps hold down sand scratches, and provides color uniformity for the basecoat color.

Surface Preparation:

Old paint well sanded and surfaces well primed and prepared.

Suitable Substrates:


- Existing Finishes except TPA
- **“General”** 1 K or 2 K primers
- OEM Primer or EDP, sanded
- **“General”** Polyester Putties
- Bare metal substrates must be pre-primed with wash primer **9700**



100% “Genrock” thinners (as a clear sealer)

Mix one (1) part 800TS Sealer with one (1) to (2) parts 700 Series Tints (depending on color opacity). Reduce 75% with appropriate speed GenRock Reducer.

Mix one (1) part 800TS to one (1) part GenRock Reducer to use as a clear sealer.




18-19 sec / DIN 4 mm / 20 °C (68 °F)



Compliant 1.4– 1.5 mm
2.0 – 2.5 bar inlet pressure
HVLP 1.4 – 1.5 mm; 0.7 bars at the air-cap
8 – 12 microns per coat



5 min. between coats.



Wait until fully matt before applying top coat.



800TS 1K Tintable Sealer

Flash Point: 27°C

Specific Gravity: 1.09 kg/cm³

Solids Content: 42 % by weight

Coverage: 8 – 10 m²/l at 25 micron dry thickness

SDS: See the safety data sheet