Printing date 09/11/2019

Reviewed on 06/28/2019

Page 1/14

1 Identification

- · Product identifier
- · Trade name: 3021 VOC SMOOTH CLEAR
- · Article number: 3021
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: General Paint Co. S.A.L. P.O. Box 7623 Beirut LEBANON info@generalpaint.biz
- Information department: Product Safety Department
 Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

· Classification of the substance or mixture

GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

GHS07

Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2A	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H336	May cause drowsiness or dizziness.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



· Signal word Danger

 Hazard-determining components of labeling: acetone n-butyl acetate

(Contd. on page 2)

US

Page 2/14

Safety Data Sheet acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 3021 VOC SMOOTH CLEAR

(Contd. of page 1) methyl methacrylate bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate 2.3-epoxypropyl neodecanoate s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-· Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness. Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Wash contaminated clothing before reuse. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 2Fire = 3



(Contd. on page 3)

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 3021 VOC SMOOTH CLEAR

· HMIS-ratings (scale 0 - 4)

 HEALTH
 2
 Health = 2

 FIRE
 3
 Fire = 3

 REACTIVITY 0
 Reactivity = 0

· Other hazards

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous o	components:	
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	>25- <i>≤</i> 50%
67-64-1	acetone	>10- <i>≤</i> 25%
123-86-4	n-butyl acetate	>10- <i>≤</i> 25%
80-62-6	methyl methacrylate	<i>≦</i> 2.5%
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	<i>≤</i> 2.5%
	2,3-epoxypropyl neodecanoate	<i>≤</i> 2.5%
104810-47-1	s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol- ohydroxypoly(oxyethylene);a-3-(3-(2h-	<i>≤</i> 2.5%

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 4)

US





(Contd. of page 2)

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 3021 VOC SMOOTH CLEAR

• Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
67-64-1	acetone	200 ppm
123-86-4	n-butyl acetate	5 ppm
80-62-6	methyl methacrylate	17 ppm
868-77-9	2-hydroxyethyl methacrylate	1.9 mg/m ³
79-41-4	methacrylic acid	6.7 ppm
77-58-7	dibutyltin dilaurate	1.1 mg/m ³
556-67-2	octamethylcyclotetrasiloxane	30 ppm
· PAC-2:		
67-64-1	acetone	3200* ppm
123-86-4	n-butyl acetate	200 ppm
80-62-6	methyl methacrylate	120 ppm
868-77-9	2-hydroxyethyl methacrylate	21 mg/m ³
		(Contd. on page 5



Page 4/14

(Contd. of page 3)

Printing date 09/11/2019

Reviewed on 06/28/2019

Page 5/14

Trade name: 3021 VOC SMOOTH CLEAR

		(Contd. of page 4)
	methacrylic acid	61 ppm
77-58-7	dibutyltin dilaurate	8 mg/m³
556-67-2	octamethylcyclotetrasiloxane	68 ppm
· PAC-3:		
67-64-1	acetone	5700* ppm
123-86-4	n-butyl acetate	3000* ppm
80-62-6	methyl methacrylate	570 ppm
868-77-9	2-hydroxyethyl methacrylate	1,000 mg/m³
79-41-4	methacrylic acid	220 ppm
77-58-7	dibutyltin dilaurate	48 mg/m ³
556-67-2	octamethylcyclotetrasiloxane	130 ppm

7 Handling and storage

- · Handling:
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.


(Contd. on page 6)

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 3021 VOC SMOOTH CLEAR

	(Contd. of page 5)
	4-1 acetone
PEL	Long-term value: 2400 mg/m³, 1000 ppm
REL	Long-term value: 590 mg/m³, 250 ppm
TLV	Short-term value: 1187 mg/m³, 500 ppm
	Long-term value: 594 mg/m³, 250 ppm
	BEI
	86-4 n-butyl acetate
	Long-term value: 710 mg/m³, 150 ppm
REL	Short-term value: 950 mg/m³, 200 ppm
	Long-term value: 710 mg/m³, 150 ppm
TLV	- · · · · · · · · · · · · · · · · · · ·
	Long-term value: 238 mg/m³, 50 ppm
	2-6 methyl methacrylate
	Long-term value: 410 mg/m³, 100 ppm
REL	Long-term value: 410 mg/m³, 100 ppm
TLV	Short-term value: 410 mg/m³, 100 ppm
	Long-term value: 205 mg/m³, 50 ppm
	DSEN
Ingre	edients with biological limit values:
	4-1 acetone
	50 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Acetone (nonspecific)
	itional information: The lists that were valid during the creation were used as basis.
	osure controls
	onal protective equipment:
	eral protective and hygienic measures: a way from foodstuffs, beverages and feed.
	ediately remove all soiled and contaminated clothing.
	h hands before breaks and at the end of work.
	d contact with the eyes and skin.
	thing equipment:
	se of brief exposure or low pollution use respiratory filter device. In case of intensive or longe
	sure use respiratory protective device that is independent of circulating air.
Prote	ection of hands:
	Protective gloves
V	
The g	glove material has to be impermeable and resistant to the product/ the substance/ the preparation (Contd. on page 7



Page 6/14



Page 7/14

Safety Data Sheet acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 3021 VOC SMOOTH CLEAR

(Contd. of page 6)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material** The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

Appearance:	
Form:	Liquid
Color:	Clear
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 55 °C (131 °F)
Flash point:	-5 °C (23 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	370 °C (698 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air vapor mixtures are possible.



Printing date 09/11/2019

Reviewed on 06/28/2019

Page 8/14

Trade name: 3021 VOC SMOOTH CLEAR

		(Contd. of page
Explosion limits:		
Lower:	1.2 Vol %	
Upper:	13 Vol %	
Vapor pressure at 20 °C (68 °F):	233 hPa (174.8 mm Hg)	
Density at 20 °C (68 °F):	1.1 g/cm³ (9.1795 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wat	er): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	73.2 %	
Coating VOC content:	10.05 %	
5	280.7 g/l / 2.34 lb/gal	
Material VOC content:	110.6 g/l / 0.92 lb/gal	
Solids content:	26.0 %	
Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

· Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.

(Contd. on page 9)

US





Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 3021 VOC SMOOTH CLEAR

• on the eye: Irritating effect.

· Sensitization: Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

Carcinogenic categories

· IARC (International Agency for Research on Cancer)

80-62-6 methyl methacrylate

· NTP (National Toxicology Program)

None of the ingredients is listed.

- · OSHA-Ca (Occupational Safety & Health Administration)
- None of the ingredients is listed.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 10)



(Contd. of page 8)

3

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 3021 VOC SMOOTH CLEAR

(Contd. of page 9)

Uncleaned packagings:
 Recommendation: Disposal must be made according to official regulations.

UN-Number DOT, ADR, IMDG, IATA	UN1263
UN proper shipping name DOT ADR IMDG, IATA	Paint 1263 PAINT, ENVIRONMENTALLY HAZARDOUS PAINT
Transport hazard class(es)	
DOT	
Class	3 Flammable liquids
Label	3
Class	3 Flammable liquids
Label	3
Packing group DOT, ADR, IMDG, IATA	11
Environmental hazards: Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
Danger code (Kemler):	33
EMS Number: Stowage Category	F-E, <u>S-E</u> B
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.





Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 3021 VOC SMOOTH CLEAR

	(Contd. of page 1
• Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
ADR	
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1263 PAINT, 3, II, ENVIRONMENTALL HAZARDOUS

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

None of the in	ngredients is listed.	
Section 313	(Specific toxic chemical listings):	
80-62-6 metl	hyl methacrylate	
TSCA (Toxic	Substances Control Act):	
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	ACTIV
67-64-1	acetone	ACTIVI
123-86-4	n-butyl acetate	ACTIV
9004-36-8	cellulose acetate butyrate	ACTIV
80-62-6	methyl methacrylate	ACTIV
41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	ACTIV
26761-45-5	2,3-epoxypropyl neodecanoate	ACTIV
104810-47-1	s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol- ohydroxypoly(oxyethylene);a-3-(3-(2h-	ACTIVI
868-77-9	2-hydroxyethyl methacrylate	ACTIVI
79-41-4	methacrylic acid	ACTIV
82919-37-7	methyl 1,2,2,6,66prntamethyl-4-piperidyl sebacate	ACTIVI





Printing date 09/11/2019

Reviewed on 06/28/2019

Page 12/14

Trade name: 3021 VOC SMOOTH CLEAR

ACTIVE
ACTIVE
1
E, NL
A4
A4
A4
-

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labeling:

acetone n-butyl acetate methyl methacrylate bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate

(Contd. on page 13)

Page 13/14

(Contd. of page 12)

Safety Data Sheet acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 3021 VOC SMOOTH CLEAR

2.3-epoxypropyl neodecanoate s-3-(3-(2h-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionol-ohydroxypoly(oxyethylene);a-3-(3-(2h-· Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Causes serious eve irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Wash contaminated clothing before reuse. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product safety department

· Contact: N/A

· Date of preparation / last revision 09/11/2019 / -

(Contd. on page 14)

US

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 3021 VOC SMOOTH CLEAR

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, ÉU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Skin Sens. 1: Skin sensitisation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 US



Page 14/14

(Contd. of page 13)