



Printing date 09/11/2019

Reviewed on 05/06/2019

1 Identification

· Product identifier

· Trade name: GO377 XIRALLIC GREEN

· Article number: GO377

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: General Paint Co. S.A.L.

P.O. Box 7623

Beirut

LEBANON

info@generalpaint.biz

· Information department: Product Safety Department

· Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Liq. 4 H227 Combustible liquid.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- Hazard pictograms Void
- · Signal word Warning
- · Hazard statements

Combustible liquid.

· Precautionary statements

Keep away from flames and hot surfaces. - No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0 Fire = 2Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0Fire = 2

Reactivity = 0

(Contd. on page 2)





Printing date 09/11/2019 Reviewed on 05/06/2019

Trade name: GO377 XIRALLIC GREEN

(Contd. of page 1)

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

111-76-2 2-butoxyethanol

>2.5-*≤*10%

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
 - CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

(Contd. on page 3)





Printing date 09/11/2019 Reviewed on 05/06/2019

Trade name: GO377 XIRALLIC GREEN

(Contd. of page 2)

Ensure adequate ventilation.

Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:			
111-76-2	2-butoxyethanol	60 ppm	
67-63-0	propan-2-ol	400 ppm	
108-01-0	2-dimethylaminoethanol	3.7 ppm	
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm	
1330-20-7	xylene	130 ppm	
100-41-4	ethylbenzene	33 ppm	
140-88-5	ethyl acrylate	8.3 ppm	
· PAC-2:			
111-76-2	2-butoxyethanol	120 ppm	
67-63-0	propan-2-ol	2000* ppm	
108-01-0	2-dimethylaminoethanol	40 ppm	
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm	
1330-20-7	xylene	920* ppm	
100-41-4	ethylbenzene	1100* ppm	
140-88-5	ethyl acrylate		
· PAC-3:			
111-76-2	2-butoxyethanol	700 ppm	
67-63-0	propan-2-ol	12000** ppm	
108-01-0	2-dimethylaminoethanol	72 ppm	
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm	
1330-20-7	xylene	2500* ppm	
100-41-4	ethylbenzene	1800* ppm	
140-88-5	ethyl acrylate	240 ppm	

7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

(Contd. on page 4)





Printing date 09/11/2019 Reviewed on 05/06/2019

Trade name: GO377 XIRALLIC GREEN

(Contd. of page 3)

- Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 10
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

111-76-2 2-butoxyethanol

PEL Long-term value: 240 mg/m³, 50 ppm

Skin

REL Long-term value: 24 mg/m³, 5 ppm

Skin

TLV Long-term value: 97 mg/m³, 20 ppm

BEI

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BEI 200 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Butoxyacetic acid with hydrolysis

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Breathing equipment: Not required.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5)





Printing date 09/11/2019 Reviewed on 05/06/2019

Trade name: GO377 XIRALLIC GREEN

· Material of gloves

(Contd. of page 4)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

9 Physical and chemical properties

· Information on basic physical and o · General Information	chemical properties
· Appearance:	-
Form:	Fluid
Color:	According to product description
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C (212 °F)
· Flash point:	68 °C (154.4 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	240 °C (464 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Not determined.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
· Density at 20 °C (68 °F):	1.075 g/cm³ (8.97088 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.

(Contd. on page 6)





Printing date 09/11/2019 Reviewed on 05/06/2019

Trade name: GO377 XIRALLIC GREEN

		(Contd. of page
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/	water): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	8.7 %	
Water:	70.2 %	
Coating VOC content:	8.73 %	
•	383.1 g/l / 3.20 lb/gal	
Material VOC content:	93.9 g/l / 0.78 lb/gal	
Solids content:	20.7 %	
Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories

· IARC (Inte	rnational Agency for Research on Cancer)	
111-76-2	2-butoxyethanol	3
67-63-0	propan-2-ol	3
	(Conto	d. on page 7)

US





Printing date 09/11/2019 Reviewed on 05/06/2019

Trade name: GO377 XIRALLIC GREEN

		(Contd. of	page 6)	
	1330-20-7		3	
		ethylbenzene	2B	
	140-88-5	ethyl acrylate	2B	
	· NTP (National Toxicology Program)			
l	None of the ingredients is listed.			
	· OSHA-Ca (Occupational Safety & Health Administration)			
	None of the	e ingredients is listed.		

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information		
· UN-Number	NOT APPLICABLE	
· UN proper shipping name	NOT APPLICABLE	
		(Contd. on page 8)

____U





Printing date 09/11/2019 Reviewed on 05/06/2019

Trade name: GO377 XIRALLIC GREEN

		(Contd. of page 7)
· Transport hazard class(es)	NOT APPLICABLE	
· Packing group	NOT APPLICABLE	
· Environmental hazards: · Marine pollutant:	No	
· Special precautions for user	Not applicable.	
· Transport in bulk according to Anne. MARPOL73/78 and the IBC Code	x II of Not applicable.	

15 Regulatory information

140-88-5 ethyl acrylate

- · Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara		
· Section 35	55 (extremely hazardous substances):	
None of the	e ingredients is listed.	
· Section 31	13 (Specific toxic chemical listings):	
111-76-2	2-butoxyethanol	
67-63-0	propan-2-ol	
1330-20-7	xylene	
100-41-4	ethylbenzene	
140-88-5	ethyl acrylate	
· TSCA (To	xic Substances Control Act):	
111-76-2	2-butoxyethanol	ACTIVE
67-63-0	propan-2-ol	ACTIVE
108-01-0	2-dimethylaminoethanol	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
1330-20-7	xylene	ACTIVE
100-41-4	ethylbenzene	ACTIVE
140-88-5	ethyl acrylate	ACTIVE
7732-18-5	water, distilled, conductivity or of similar purity	ACTIVE
Hazardou	s Air Pollutants	
1330-20-7	xylene	
100-41-4	ethylbenzene	

(Contd. on page 9)





Printing date 09/11/2019 Reviewed on 05/06/2019

Trade name: GO377 XIRALLIC GREEN

(Contd. of page 8)

· Proposition 65

· Chemica	ils ki	nown	to	cause	cancer:

100-41-4 ethylbenzene

140-88-5 ethyl acrylate

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)		
111-76-2	2-butoxyethanol	NL
1330-20-7	xylene	I
100-41-4	ethylbenzene	D

· TLV (Threshold Limit Value established by ACGIH)			
	2-butoxyethanol	<i>A</i> 3	
	propan-2-ol	A4	
1330-20-7		A4	
100-41-4	ethylbenzene	A3	
140-88-5	ethyl acrylate	A4	

· NIOSH-Ca (National Institute for Occupational Safety and Health)

140-88-5 ethyl acrylate

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

- · Hazard pictograms Void
- · Signal word Warning
- · Hazard statements

Combustible liquid.

· Precautionary statements

Keep away from flames and hot surfaces. - No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

LIS



Page 10/10

Safety Data Sheet acc. to OSHA HCS

Printing date 09/11/2019 Reviewed on 05/06/2019

Trade name: GO377 XIRALLIC GREEN

(Contd. of page 9)

6 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 09/11/2019 / -
- · Abbreviations and acronyms:

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 4: Flammable liquids - Category 4