



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 05/06/2019

1 Identification

- **Product identifier**
- **Trade name:** GO995 METALLIC FINE
- **Article number:** GO995
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
General Paint Co. S.A.L.
P.O. Box 7623
Beirut
LEBANON
info@generalpaint.biz
- **Information department:** Product Safety Department
- **Emergency telephone number:** 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

- **Classification of the substance or mixture**
Flam. Liq. 4 H227 Combustible liquid.
- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms** Void
- **Signal word** Warning
- **Hazard statements**
Combustible liquid.
- **Precautionary statements**
Keep away from flames and hot surfaces. – No smoking.
Wear protective gloves/protective clothing/eye protection/face protection.
In case of fire: Use for extinction: CO2, powder or water spray.
Store in a well-ventilated place. Keep cool.
Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



Health = 0
Fire = 2
Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



Health = 0
Fire = 2
Reactivity = 0

(Contd. on page 2)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 05/06/2019

Trade name: GO995 METALLIC FINE

(Contd. of page 1)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

111-76-2	2-butoxyethanol	>2.5-≤10%
7429-90-5	aluminium powder (stabilised)	>2.5-≤10%
67-63-0	propan-2-ol	≤2.5%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 05/06/2019

Trade name: GO995 METALLIC FINE

(Contd. of page 2)

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals**· PAC-1:**

111-76-2	2-butoxyethanol	60 ppm
67-63-0	propan-2-ol	400 ppm
108-01-0	2-dimethylaminoethanol	3.7 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
1330-20-7	xylene	130 ppm
100-41-4	ethylbenzene	33 ppm
140-88-5	ethyl acrylate	8.3 ppm

· PAC-2:

111-76-2	2-butoxyethanol	120 ppm
67-63-0	propan-2-ol	2000* ppm
108-01-0	2-dimethylaminoethanol	40 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
1330-20-7	xylene	920* ppm
100-41-4	ethylbenzene	1100* ppm
140-88-5	ethyl acrylate	36 ppm

· PAC-3:

111-76-2	2-butoxyethanol	700 ppm
67-63-0	propan-2-ol	12000** ppm
108-01-0	2-dimethylaminoethanol	72 ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800* ppm
140-88-5	ethyl acrylate	240 ppm

7 Handling and storage

· Handling:

· Precautions for safe handling No special precautions are necessary if used correctly.

(Contd. on page 4)



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 05/06/2019

Trade name: GO995 METALLIC FINE

(Contd. of page 3)

- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 10
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

111-76-2 2-butoxyethanol

PEL	Long-term value: 240 mg/m ³ , 50 ppm Skin
REL	Long-term value: 24 mg/m ³ , 5 ppm Skin
TLV	Long-term value: 97 mg/m ³ , 20 ppm BEI

67-63-0 propan-2-ol

PEL	Long-term value: 980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV	Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 492 mg/m ³ , 200 ppm BEI

- **Ingredients with biological limit values:**

111-76-2 2-butoxyethanol

BEI	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis
-----	--

(Contd. on page 5)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 05/06/2019

Trade name: GO995 METALLIC FINE

(Contd. of page 4)

67-63-0 propan-2-ol

BEI	40 mg/L
Medium:	urine
Time:	end of shift at end of workweek
Parameter:	Acetone (background, nonspecific)

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:** Wash hands before breaks and at the end of work.
- **Breathing equipment:** Not required.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:** Goggles recommended during refilling.

9 Physical and chemical properties

Information on basic physical and chemical properties**General Information****Appearance:****Form:**

Fluid

Color:

According to product description

Odor:

Characteristic

Odor threshold:

Not determined.

pH-value:

Not determined.

Change in condition**Melting point/Melting range:**

Undetermined.

(Contd. on page 6)

**Safety Data Sheet**
acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 05/06/2019

Trade name: GO995 METALLIC FINE

(Contd. of page 5)

Boiling point/Boiling range:	100 °C (212 °F)
· Flash point:	68 °C (154.4 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	240 °C (464 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Not determined.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
· Density at 20 °C (68 °F):	1.025 g/cm ³ (8.55363 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	9.0 %
Water:	73.2 %
Coating VOC content:	9.00 %
	368.7 g/l / 3.08 lb/gal
Material VOC content:	92.2 g/l / 0.77 lb/gal
· Solids content:	17.6 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.

(Contd. on page 7)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 05/06/2019

Trade name: GO995 METALLIC FINE

(Contd. of page 6)

- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

111-76-2	2-butoxyethanol	3
67-63-0	propan-2-ol	3
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
140-88-5	ethyl acrylate	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 8)

US



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 05/06/2019

Trade name: GO995 METALLIC FINE

(Contd. of page 7)

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|--|-----------------|
| · UN-Number | NOT APPLICABLE |
| · UN proper shipping name | NOT APPLICABLE |
| · Transport hazard class(es) | NOT APPLICABLE |
| · Packing group | NOT APPLICABLE |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Not applicable. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

111-76-2	2-butoxyethanol
67-63-0	propan-2-ol
1330-20-7	xylene
100-41-4	ethylbenzene
140-88-5	ethyl acrylate

(Contd. on page 9)



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 05/06/2019

Trade name: GO995 METALLIC FINE

(Contd. of page 8)

· TSCA (Toxic Substances Control Act):

111-76-2	2-butoxyethanol	ACTIVE
67-63-0	propan-2-ol	ACTIVE
108-01-0	2-dimethylaminoethanol	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
1330-20-7	xylene	ACTIVE
100-41-4	ethylbenzene	ACTIVE
140-88-5	ethyl acrylate	ACTIVE
7732-18-5	water, distilled, conductivity or of similar purity	ACTIVE

· Hazardous Air Pollutants

1330-20-7	xylene
100-41-4	ethylbenzene
140-88-5	ethyl acrylate

· Proposition 65**· Chemicals known to cause cancer:**

100-41-4	ethylbenzene
140-88-5	ethyl acrylate

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories**· EPA (Environmental Protection Agency)**

111-76-2	2-butoxyethanol	NL
1330-20-7	xylene	I
100-41-4	ethylbenzene	D

· TLV (Threshold Limit Value established by ACGIH)

111-76-2	2-butoxyethanol	A3
67-63-0	propan-2-ol	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
140-88-5	ethyl acrylate	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

140-88-5	ethyl acrylate
----------	----------------

(Contd. on page 10)



Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 05/06/2019

Trade name: GO995 METALLIC FINE

(Contd. of page 9)

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms Void**· Signal word** Warning**· Hazard statements**

Combustible liquid.

· Precautionary statements

Keep away from flames and hot surfaces. – No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

In case of fire: Use for extinction: CO₂, powder or water spray.

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product safety department**· Contact:** N/A**· Date of preparation / last revision** 09/11/2019 / -**· Abbreviations and acronyms:**

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 4: Flammable liquids – Category 4