
Printing date 09/11/2019

Reviewed on 06/28/2019

#### 1 Identification

- · Product identifier
- · Trade name: 711 LUMINOUS BLUE
- · Article number: 711
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: General Paint Co. S.A.L. P.O. Box 7623 Beirut LEBANON info@generalpaint.biz
- Information department: Product Safety Department
   Emergency telephone number: 1-800-535-5053 contract number (89244)

#### 2 Hazard(s) identification





Printing date 09/11/2019

Reviewed on 06/28/2019

#### Trade name: 711 LUMINOUS BLUE

(Contd. of page 1) · Hazard pictograms GHS02 GHS07 GHS08 · Signal word Warning Hazard-determining components of labeling: n-butyl acetate ethylbenzene · Hazard statements Flammable liquid and vapor. Causes skin irritation. Suspected of causing cancer. May cause drowsiness or dizziness. May cause damage to the hearing organs through prolonged or repeated exposure. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. (Contd. on page 3) US



Page 2/14

*Printing date 09/11/2019* 

Reviewed on 06/28/2019

#### Trade name: 711 LUMINOUS BLUE

Classification system:
 NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)



#### · Other hazards

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

#### 3 Composition/information on ingredients

#### · Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
	n-butyl acetate	>50- <i>≤</i> 100%
1330-20-7	xylene	>10- <i>≤</i> 25%
108-65-6	2-methoxy-1-methylethyl acetate	>2.5- <i>≤</i> 10%
100-41-4	ethylbenzene	<i>≤</i> 2.5%
64742-95-6	Solvent naphtha (petroleum), light arom.	<i>≤</i> 2.5%

#### 4 First-aid measures

- · Description of first aid measures
- General information:
- Immediately remove any clothing soiled by the product.
- Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 4)

US



(Contd. of page 2)



Printing date 09/11/2019

Reviewed on 06/28/2019

#### Trade name: 711 LUMINOUS BLUE

• Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

#### 6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- Reference to other sections
   See Section 7 for information on safe handling.
   See Section 8 for information on personal protection equipment.
   See Section 13 for disposal information.
   Protective Action Criteria for Chemicale

### Protective Action Criteria for Chemicals

123-86-4	n-butyl acetate	5 ppm
1330-20-7	xylene	130 ppn
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
100-41-4	ethylbenzene	33 ppm
111-76-2	2-butoxyethanol	60 ppm
107-98-2	1-methoxy-2-propanol	100 ppn
70657-70-4	2-methoxypropyl acetate	50 ppm
PAC-2:		
123-86-4	n-butyl acetate	200 ppm
1330-20-7	xylene	920* ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppn
		(Contd. on page



Page 4/14

(Contd. of page 3)

US

*Printing date 09/11/2019* 

Reviewed on 06/28/2019

Page 5/14

#### Trade name: 711 LUMINOUS BLUE

		(Contd. of page 4)	
	ethylbenzene	1100* ppm	
111-76-2	2-butoxyethanol	120 ppm	
107-98-2	1-methoxy-2-propanol	160 ppm	
70657-70-4	2-methoxypropyl acetate	1,000 ppm	
· PAC-3:	· PAC-3:		
123-86-4	n-butyl acetate	3000* ppm	
1330-20-7	xylene	2500* ppm	
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm	
100-41-4	ethylbenzene	1800* ppm	
111-76-2	2-butoxyethanol	700 ppm	
107-98-2	1-methoxy-2-propanol	660 ppm	
70657-70-4	2-methoxypropyl acetate	5,000 ppm	

#### 7 Handling and storage

- · Handling:
- Precautions for safe handling
   Ensure good ventilation/exhaustion at the workplace.
   Open and handle receptacle with care.
   Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
   Protect against electrostatic charges.
   Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
   Storage class: 3
- Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

- · Control parameters
- Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

(Contd. on page 6)



Printing date 09/11/2019

Reviewed on 06/28/2019

#### Trade name: 711 LUMINOUS BLUE

400 0	(Contd. of pa
	36-4 n-butyl acetate
PEL	Long-term value: 710 mg/m³, 150 ppm
REL	Short-term value: 950 mg/m³, 200 ppm
	Long-term value: 710 mg/m³, 150 ppm
TLV	Short-term value: 712 mg/m <sup>3</sup> , 150 ppm
	Long-term value: 238 mg/m <sup>3</sup> , 50 ppm
1330-	-20-7 xylene
PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 655 mg/m³, 150 ppm
	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: 651 mg/m³, 150 ppm
	Long-term value: 434 mg/m <sup>3</sup> , 100 ppm
	BEI
	5-6 2-methoxy-1-methylethyl acetate
WEEI	L Long-term value: 50 ppm
100-4	11-4 ethylbenzene
PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 545 mg/m³, 125 ppm
	Long-term value: 435 mg/m³, 100 ppm
TLV	Long-term value: 87 mg/m³, 20 ppm
	BEI
Ingre	dients with biological limit values:
1330-	-20-7 xylene
	1.5 g/g creatinine
	Medium: urine
	Time: end of shift
	Parameter: Methylhippuric acids
	11-4 ethylbenzene
	0.7 g/g creatinine
	Medium: urine
	Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
ľ	
-	Medium: end-exhaled air
-	Time: not critical
	Parameter: Ethyl benzene (semi-quantitative)
· · ·	tional information: The lists that were valid during the creation were used as basis.
۰، ۲	<b>Signal information:</b> The lists that were valid during the creation were used as begin



Page 6/14

Page 7/14

#### Safety Data Sheet acc. to OSHA HCS

*Printing date 09/11/2019* 

Reviewed on 06/28/2019

#### Trade name: 711 LUMINOUS BLUE

(Contd. of page 6)

- Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the skin. Avoid contact with the eyes and skin.
- · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

#### 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:
  - Form: Color:

Liquid Light blue

(Contd. on page 8)

US

Printing date 09/11/2019

Reviewed on 06/28/2019

#### Trade name: 711 LUMINOUS BLUE

	(Contd. of page 7
· Odor: · Odor threshold:	Characteristic Not determined.
· pH-value:	Not determined.
<ul> <li>Change in condition Melting point/Melting range: Boiling point/Boiling range:</li> </ul>	Undetermined. 124 °C (255.2 °F)
· Flash point:	27 °C (80.6 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	315 °C (599 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air, vapor mixtures are possible.
<ul> <li>Explosion limits: Lower: Upper:</li> </ul>	1.1 Vol % 7.5 Vol %
<ul> <li>Vapor pressure at 20 °C (68 °F):</li> </ul>	10.7 hPa (8 mm Hg)
<ul> <li>Density at 20 °C (68 °F):</li> <li>Relative density</li> <li>Vapor density</li> <li>Evaporation rate</li> </ul>	0.972 g/cm <sup>3</sup> (8.11134 lbs/gal) Not determined. Not determined. Not determined.
<ul> <li>Solubility in / Miscibility with Water:</li> </ul>	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	r): Not determined.
<ul> <li>Viscosity:</li> <li>Dynamic:</li> <li>Kinematic:</li> </ul>	Not determined. Not determined.
<ul> <li>Solvent content: Organic solvents: Coating VOC content:</li> <li>Material VOC content:</li> </ul>	72.7 % 72.69 % 706.6 g/l / 5.90 lb/gal 706.6 g/l / 5.90 lb/gal
Solids content: • Other information	27.3 % No further relevant information available.

Page 8/14



Printing date 09/11/2019

Reviewed on 06/28/2019

#### Trade name: 711 LUMINOUS BLUE

#### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

#### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

#### · LD/LC50 values that are relevant for classification:

1330-20-7 xylene

#### Oral LD50 4,300 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

#### · Primary irritant effect:

- on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

#### · Carcinogenic categories

· IARC (Inte	rnational Agency for Research on Cancer)	
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
111-76-2	2-butoxyethanol	3
· NTP (Natio	onal Toxicology Program)	
None of the	e ingredients is listed.	
· OSHA-Ca	(Occupational Safety & Health Administration)	
None of the	e ingredients is listed.	

(Contd. on page 10)



(Contd. of page 8)

Page 9/14

*Printing date 09/11/2019* 

Reviewed on 06/28/2019

#### Trade name: 711 LUMINOUS BLUE

#### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:

#### · General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

#### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number		
DOT, ADR, IMDG, IATA	UN1263	
UN proper shipping name		
DOT	Paint	
ADR	1263 PAINT	
IMDG, IATA	PAINT	



(Contd. of page 9)

Page 10/14

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 711 LUMINOUS BLUE

	(Contd. of page
Transport hazard class(es)	
DOT	
P.Minet 1990	
2	
Class	3 Flammable liquids
Label	3
ADR, IMDG, IATA	
•	
Class	3 Flammable liquids
Label	3
Packing group	
DOT, ADR, IMDG, IATA	111
Environmental hazards:	A 1
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
EMS Number:	F-E, <u>S-E</u> A
Stowage Category	
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	
	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 60 L
	On cargo aircraft only: 220 L
ADR	Octor F4
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inper packaging: 30 ml
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
IMDG Limited quantities (LQ)	5L
Excepted quantities (EQ)	SL Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
	(Contd. on page



Page 11/14

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 711 LUMINOUS BLUE

· UN "Model Regulation":

UN 1263 PAINT, 3, III

#### 15 Regulatory information

 $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  Sara

5 (extremely hazardous substances):			
ingredients is listed.			
3 (Specific toxic chemical listings):			
xylene			
ethylbenzene			
2-butoxyethanol			
ic Substances Control Act):			
n-butyl acetate	ACTIVE		
xylene	ACTIVE		
2-methoxy-1-methylethyl acetate	ACTIVE		
ethylbenzene	ACTIVE		
2-butoxyethanol	ACTIVE		
1-methoxy-2-propanol	ACTIVE		
Hazardous Air Pollutants			
xylene			
100-41-4 ethylbenzene			
· Proposition 65			
known to cause cancer:			
100-41-4 ethylbenzene			
Chemicals known to cause reproductive toxicity for females:			
None of the ingredients is listed.			
known to cause reproductive toxicity for males:			
ingredients is listed.			
known to cause developmental toxicity:			
None of the ingredients is listed.			
	ingredients is listed. 3 (Specific toxic chemical listings): xylene ethylbenzene 2-butoxyethanol ic Substances Control Act): n-butyl acetate xylene 2-methoxy-1-methylethyl acetate ethylbenzene 2-butoxyethanol 1-methoxy-2-propanol Air Pollutants xylene ethylbenzene n 65 known to cause cancer: thylbenzene known to cause reproductive toxicity for females: ingredients is listed. known to cause reproductive toxicity for males: ingredients is listed. known to cause developmental toxicity:		

#### · Carcinogenic categories

· EPA (Environmental Protection Agency)

1330-20-7 xylene

100-41-4 ethylbenzene

(Contd. on page 13)



(Contd. of page 11)

Page 12/14

D age 13)

1

Page 13/14

(Contd. of page 12)

NL

A4

A3

AЗ

#### Safety Data Sheet acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

#### Trade name: 711 LUMINOUS BLUE

111 70 0	0 hutan athanal
111-70-2	2-butoxyethanol

#### · TLV (Threshold Limit Value established by ACGIH)

1330-20-7 xylene

100-41-4 ethylbenzene

111-76-2 2-butoxyethanol

#### · NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



#### · Signal word Warning

· Hazard-determining components of labeling: *n*-butyl acetate ethylbenzene · Hazard statements Flammable liquid and vapor. Causes skin irritation. Suspected of causing cancer. May cause drowsiness or dizziness. May cause damage to the hearing organs through prolonged or repeated exposure. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Get medical advice/attention if you feel unwell.

(Contd. on page 14)

us

Page 14/14

(Contd. of page 13)

### Safety Data Sheet acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

#### Trade name: 711 LUMINOUS BLUE

If skin irritation occurs: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations. • Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product safety department

· Contact: N/A

- · Date of preparation / last revision 09/11/2019 / -
- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, ÉU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

US