



Printing date 06/15/2020

Reviewed on 05/29/2020

1 Identification

- · Product identifier
- · Trade name: 741 RED LUMINA
- · Article number: 741
- · Application of the substance / the mixture refer to the relevant Technical Data Sheet
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

General Paint Co. S.A.L.

P.O. Box 7623

Beirut

LEBANON

info@generalpaint.biz

- · Information department: Product Safety Department
- Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07 GHS08

(Contd. on page 2)





Reviewed on 05/29/2020 Printing date 06/15/2020

Trade name: 741 RED LUMINA

(Contd. of page 1)

· Signal word Warning

· Hazard-determining components of labeling:

n-butyl acetate ethylbenzene

· Hazard statements

Flammable liquid and vapor.

Suspected of causing cancer.

May cause drowsiness or dizziness.

May cause damage to the hearing organs through prolonged or repeated exposure.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 0Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0Fire = 3

Reactivity = 0

· Other hazards

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 3)





Printing date 06/15/2020 Reviewed on 05/29/2020

Trade name: 741 RED LUMINA

· vPvB: Not applicable.

(Contd. of page 2)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description**: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
123-86-4	n-butyl acetate	>50-≤100%
1330-20-7	xylene	>2.5-≤10%
	Solvent naphtha (petroleum), light arom.	>2.5-≤10%
108-65-6	2-methoxy-1-methylethyl acetate	>2.5-≤10%
111-76-2	2-butoxyethanol	<i>≤</i> 2.5%
100-41-4	ethylbenzene	<i>≤</i> 2.5%

4 First-aid measures

- · Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)





Printing date 06/15/2020 Reviewed on 05/29/2020

Trade name: 741 RED LUMINA

(Contd. of page 3)

- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

PAC-1:			
	n-butyl acetate	5 ppm	
1330-20-7	xylene	130 ppr	
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm	
111-76-2	2-butoxyethanol	60 ppm	
100-41-4	ethylbenzene	33 ppm	
107-98-2	1-methoxy-2-propanol	100 ppr	
70657-70-4	2-methoxypropyl acetate	50 ppm	
PAC-2:			
123-86-4	n-butyl acetate	200 ppm	
1330-20-7	xylene	920* ppm	
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppr	
111-76-2	2-butoxyethanol	120 ppm	
100-41-4	ethylbenzene	1100* ppi	
107-98-2	1-methoxy-2-propanol	160 ppm	
70657-70-4	2-methoxypropyl acetate		
PAC-3:			
123-86-4	n-butyl acetate	3000* ppi	
1330-20-7	xylene	2500* ppi	
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppr	
111-76-2	2-butoxyethanol	700 ppm	
100-41-4	ethylbenzene	1800* ppi	



Printing date 06/15/2020 Reviewed on 05/29/2020

Trade name: 741 RED LUMINA

		(Contd. of page 4)
107-98-2	1-methoxy-2-propanol	660 ppm
70657-70-4	2-methoxypropyl acetate	5,000 ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

123-86	6-4 n-butyl acetate
PEL	Long-term value: 710 mg/m³, 150 ppm
REL	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm
TLV	Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm
1330-2	20-7 xylene
PEL	Long-term value: 435 mg/m³, 100 ppm

(Contd. on page 6)





Printing date 06/15/2020 Reviewed on 05/29/2020

Trade name: 741 RED LUMINA

	(Contd. of p
REL	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm
TLV	Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI
108-6	5-6 2-methoxy-1-methylethyl acetate
WEEL	Long-term value: 50 ppm
111-7	6-2 2-butoxyethanol
PEL	Long-term value: 240 mg/m³, 50 ppm Skin
REL	Long-term value: 24 mg/m³, 5 ppm Skin
TLV	Long-term value: 97 mg/m³, 20 ppm BEI
100-4	1-4 ethylbenzene
PEL	Long-term value: 435 mg/m³, 100 ppm
REL	Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm
TLV	Long-term value: 87 mg/m³, 20 ppm BEI
Ingre	dients with biological limit values:
	dients with biological limit values: 20-7 xylene
1330- BEI 1	20-7 xylene l.5 g/g creatinine Medium: urine Time: end of shift
1330- BEI 1 N	20-7 xylene 1.5 g/g creatinine Medium: urine Fime: end of shift Parameter: Methylhippuric acids
1330- BEI 1 I I I 1111-7	20-7 xylene 1.5 g/g creatinine Medium: urine Fime: end of shift Parameter: Methylhippuric acids 6-2 2-butoxyethanol
1330- BEI 1 I F 111-7 BEI 2	20-7 xylene 1.5 g/g creatinine Medium: urine Fime: end of shift Parameter: Methylhippuric acids 16-2 2-butoxyethanol
1330- BEI 1 I F 111-7 BEI 2	20-7 xylene 1.5 g/g creatinine Medium: urine Fime: end of shift Parameter: Methylhippuric acids 6-2 2-butoxyethanol
1330- BEI 1 M 7 F 111-7 BEI 2	20-7 xylene 1.5 g/g creatinine Medium: urine Fime: end of shift Parameter: Methylhippuric acids 6-2 2-butoxyethanol 200 mg/g creatinine Medium: urine
1330- BEI 1 N F 111-7 BEI 2 N F	20-7 xylene 1.5 g/g creatinine Medium: urine Fime: end of shift Parameter: Methylhippuric acids 6-2 2-butoxyethanol 200 mg/g creatinine Medium: urine Fime: end of shift
1330- BEI 1 M 7 F 111-7 BEI 2 M 7 F	20-7 xylene 7.5 g/g creatinine Medium: urine Fime: end of shift Parameter: Methylhippuric acids 8-2 2-butoxyethanol 900 mg/g creatinine Medium: urine Fime: end of shift Parameter: Butoxyacetic acid with hydrolysis
1330- BEI 1 I I 111-7 BEI 2 I I I I I I I I I I I I I I I I I I	20-7 xylene 7.5 g/g creatinine Medium: urine Fime: end of shift Parameter: Methylhippuric acids 7.6-2 2-butoxyethanol 7.00 mg/g creatinine Medium: urine Fime: end of shift Parameter: Butoxyacetic acid with hydrolysis 7.7 g/g creatinine Medium: urine 7.7 g/g creatinine Medium: urine
1330- BEI 1 M 7 F 111-7 BEI 2 M 7 F 100-4	20-7 xylene 1.5 g/g creatinine Medium: urine Fime: end of shift Parameter: Methylhippuric acids 6-2 2-butoxyethanol 200 mg/g creatinine Medium: urine Fime: end of shift Parameter: Butoxyacetic acid with hydrolysis 1-4 ethylbenzene 2.7 g/g creatinine
1330- BEI 1 M 7 F 111-7 BEI 2 M 7 F 100-4	20-7 xylene 1.5 g/g creatinine Medium: urine Fime: end of shift Parameter: Methylhippuric acids 6-2 2-butoxyethanol 200 mg/g creatinine Medium: urine Fime: end of shift Parameter: Butoxyacetic acid with hydrolysis 1-4 ethylbenzene 1.7 g/g creatinine Medium: urine Fime: end of shift et end of workweek
1330- BEI 1 M 7 F 111-7 BEI 2 M 7 F 100-4	20-7 xylene 1.5 g/g creatinine Medium: urine Fime: end of shift Parameter: Methylhippuric acids 6-2 2-butoxyethanol 200 mg/g creatinine Medium: urine Fime: end of shift Parameter: Butoxyacetic acid with hydrolysis 1-4 ethylbenzene 1.7 g/g creatinine Medium: urine Fime: end of shift et end of workweek
1330- BEI 1 M F 111-7 BEI 2 M T F 100-4 BEI (M M	20-7 xylene 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids 16-2 2-butoxyethanol 100 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis 1-4 ethylbenzene 10.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

(Contd. on page 7)





Printing date 06/15/2020 Reviewed on 05/29/2020

Trade name: 741 RED LUMINA

(Contd. of page 6)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid Color: Red

· Odor: Characteristic

(Contd. on page 8)





Printing date 06/15/2020 Reviewed on 05/29/2020

Trade name: 741 RED LUMINA

	(Contd. of page
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 120 °C (248 °F)
Flash point:	27 °C (80.6 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	315 °C (599 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive ai vapor mixtures are possible.
Explosion limits: Lower: Upper:	1.2 Vol % 7.5 Vol %
Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
Density at 20 °C (68 °F): Relative density Vapor density Evaporation rate	0.953 g/cm³ (7.95279 lbs/gal) Not determined. Not determined. Not determined.
Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	er): Not determined.
Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
Solvent content:	74.0.0/
Organic solvents: Coating VOC content:	74.8 % 74.76 % 712.5 g/l / 5.95 lb/gal
Material VOC content:	712.5 g/l / 5.95 lb/gal
Solids content: Other information	27.8 % No further relevant information available.





Printing date 06/15/2020 Reviewed on 05/29/2020

Trade name: 741 RED LUMINA

(Contd. of page 8)

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	· LD/LC50 values that are relevant for classification:			
1330-20-7	1330-20-7 xylene			
Oral	LD50	4,300 mg/kg (rat)		
Dermal	LD50	2,000 mg/kg (rabbit)		
64742-95-	64742-95-6 Solvent naphtha (petroleum), light arom.			
Oral	LD50	>6,800 mg/kg (rat)		
Dermal	LD50	>3,400 mg/kg (rab)		
Inhalative	LC50/4 h	>10.2 mg/l (rat)		

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
1330-20-7 xylene	3	
111-76-2 2-butoxyethanol	3	
100-41-4 ethylbenzene	2B	

· NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 10)





Printing date 06/15/2020 Reviewed on 05/29/2020

Trade name: 741 RED LUMINA

(Contd. of page 9)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number

· DOT, ADR, IMDG, IATA UN1263

· UN proper shipping name

· **DOT** Paint

· **ADR** 1263 PAINT · **IMDG, IATA** PAINT

(Contd. on page 11)





Printing date 06/15/2020 Reviewed on 05/29/2020

Trade name: 741 RED LUMINA

(Contd. of page 10)

· Transport hazard class(es)

· DOT



· Class 3 Flammable liquids

· Label

· ADR, IMDG, IATA



· Class 3 Flammable liquids

· Label 3

· Packing group

· DOT, ADR, IMDG, IATA |||

· Environmental hazards:

· Marine pollutant: No

· Special precautions for user Warning: Flammable liquids

• EMS Number: F-E,S-E • Stowage Category A

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· DOT

· **Quantity limitations** On passenger aircraft/rail: 60 L

On cargo aircraft only: 220 L

· ADR

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

Maximum net quantity per outer pac

· IMDG

· Limited quantities (LQ) 5L

Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 12)





Printing date 06/15/2020 Reviewed on 05/29/2020

Trade name: 741 RED LUMINA

(Contd. of page 11)

· UN "Model Regulation": UN 1263 PAINT, 3, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

1330-20-7	xvlene
1000 20 1	AVIOLIC

111-76-2 2-butoxyethanol

100-41-4 ethylbenzene

· TSCA (Toxic Substances Control Act):

70071 (702		
		ACTIVE
1330-20-7	xylene	ACTIVE
	· · · · · · · · · · · · · · · · · · ·	ACTIVE
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
	,	ACTIVE
		ACTIVE
107-98-2	1-methoxy-2-propanol	ACTIVE

· Hazardous Air Pollutants

1330-20-7 xylene

100-41-4 ethylbenzene

- · Proposition 65
- · Chemicals known to cause cancer:

100-41-4 ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

1330-20-7 xylene

(Contd. on page 13)





Printing date 06/15/2020 Reviewed on 05/29/2020

Trade name: 741 RED LUMINA

		(Contd. of page 12)	
111-76-2	2-butoxyethanol	NL	
100-41-4	ethylbenzene	D	
· TLV (Thre	shold Limit Value established by ACGIH)		
1330-20-7	xylene	A4	
111-76-2	2-butoxyethanol	A3	
100-41-4	ethylbenzene	A3	
	· NIOSH-Ca (National Institute for Occupational Safety and Health)		
None of th	e ingredients is listed.		
011011			

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Warning

· Hazard-determining components of labeling:

n-butyl acetate ethylbenzene

Hazard statements

Flammable liquid and vapor.

Suspected of causing cancer.

May cause drowsiness or dizziness.

May cause damage to the hearing organs through prolonged or repeated exposure.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

(Contd. on page 14)





Reviewed on 05/29/2020 Printing date 06/15/2020

Trade name: 741 RED LUMINA

(Contd. of page 13)

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 06/15/2020 / -
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids - Category 3

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2