
Printing date 09/11/2019

Reviewed on 06/28/2019

1 Identification

- · Product identifier
- · Trade name: 749 FULGURANT RED
- · Article number: 749
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: General Paint Co. S.A.L. P.O. Box 7623 Beirut LEBANON info@generalpaint.biz
- Information department: Product Safety Department
 Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard(s) identification



Page 1/13

Printing date 09/11/2019

CENERAL

Reviewed on 06/28/2019

Trade name: 749 FULGURANT RED

	(Contd. of page 1)
Hazard-determining components of labeling:	
n-butyl acetate	
Hazard statements	
Flammable liquid and vapor.	
Suspected of causing cancer.	
May cause drowsiness or dizziness.	
Precautionary statements	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with wa	ater/shower
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	aler/snower.
IF exposed or concerned: Get medical advice/attention.	
Call a poison center/doctor if you feel unwell.	
In case of fire: Use for extinction: CO2, powder or water spray.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	Irogulationa
Dispose of contents/container in accordance with local/regional/national/international	regulations.
Classification system:	
NFPA ratings (scale 0 - 4)	
Health = 0	
$\frac{3}{Fire = 3}$	
$\frac{0}{0} Reactivity = 0$	
HMIS-ratings (scale 0 - 4)	
HEALTH I Health = 0	
FIRE 3 Fire = 3	
$\frac{\text{REACTIVITY}[0]}{\text{Reactivity}} = 0$	
Other hazards	
Results of PBT and vPvB assessment	
PBT: Not applicable.	
vPvB: Not applicable.	

Page 2/13

(Contd. on page 3)

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 749 FULGURANT RED

(Contd. of page 2)

Page 3/13

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

Dungereue		
123-86-4	n-butyl acetate	>50- <i>≤</i> 100%
	2-methoxy-1-methylethyl acetate	>2.5- <i>≤</i> 10%
	Solvent naphtha (petroleum), light arom.	>2.5- <i>≤</i> 10%
1330-20-7	•	>2.5- <i>≤</i> 10%
100-41-4	ethylbenzene	<i>≤</i> 2.5%

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • For safety reasons unsuitable extinguishing agents: Water with full jet

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)



Printing date 09/11/2019

Reviewed on 06/28/2019

Page 4/13

Trade name: 749 FULGURANT RED

		ontd. of page 3)		
Absorb with Dispose co Ensure add • Reference See Sectio See Sectio See Sectio	and material for containment and cleaning up: h liquid-binding material (sand, diatomite, acid binders, universal binders, sawdu ontaminated material as waste according to item 13. equate ventilation. to other sections on 7 for information on safe handling. on 8 for information on personal protection equipment. on 13 for disposal information. Action Criteria for Chemicals	ıst).		
· PAC-1:				
123-86-4	n-butyl acetate	5 ppm		
	2-methoxy-1-methylethyl acetate	50 ppm		
1330-20-7	xylene	130 ppm		
100-41-4	ethylbenzene	33 ppm		
107-98-2	1-methoxy-2-propanol	100 ppm		
· PAC-2:				
123-86-4	n-butyl acetate	200 ppm		
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm		
1330-20-7	xylene	920* ppm		
100-41-4	ethylbenzene	1100* ppm		
107-98-2	1-methoxy-2-propanol	160 ppm		
· PAC-3:				
123-86-4	n-butyl acetate	3000* ppm		
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm		
1330-20-7	xylene	2500* ppm		
100-41-4	ethylbenzene	1800* ppm		
107-98-2	1-methoxy-2-propanol	660 ppm		

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.

(Contd. on page 5)

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 749 FULGURANT RED

(Contd. of page 4)

- · Conditions for safe storage, including any incompatibilities
- · Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

123-86	-4 n-butyl acetate
PEL	Long-term value: 710 mg/m³, 150 ppm
REL	Short-term value: 950 mg/m³, 200 ppm
	Long-term value: 710 mg/m³, 150 ppm
TLV	Short-term value: 712 mg/m ³ , 150 ppm
	Long-term value: 238 mg/m³, 50 ppm
	-6 2-methoxy-1-methylethyl acetate
WEEL	Long-term value: 50 ppm
1330-2	0-7 xylene
PEL	Long-term value: 435 mg/m³, 100 ppm
REL	Short-term value: 655 mg/m³, 150 ppm
	Long-term value: 435 mg/m³, 100 ppm
TLV	Short-term value: 651 mg/m³, 150 ppm
	Long-term value: 434 mg/m³, 100 ppm
	BEI
	-4 ethylbenzene
PEL	Long-term value: 435 mg/m³, 100 ppm
REL	Short-term value: 545 mg/m³, 125 ppm
	Long-term value: 435 mg/m³, 100 ppm
TLV	Long-term value: 87 mg/m³, 20 ppm BEI
	(Contd. on page 6)



Page 5/13

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 749 FULGURANT RED

	(Contd. of page 5
Ingr	edients with biological limit values:
1330	0-20-7 xylene
BEI	1.5 g/g creatinine
	Medium: urine Time: end of shift
	Parameter: Methylhippuric acids
100	41-4 ethylbenzene
	0.7 g/g creatinine
ושכו	Medium: urine
	Time: end of shift at end of workweek
	Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
	- Medium: end-exhaled air
	Time: not critical
	Parameter: Ethyl benzene (semi-quantitative)
Add	itional information: The lists that were valid during the creation were used as basis.
Gen Keej Imm Was Stor Brea In ca expo	sonal protective equipment: eral protective and hygienic measures: b away from foodstuffs, beverages and feed. ediately remove all soiled and contaminated clothing. th hands before breaks and at the end of work. e protective clothing separately. athing equipment: ase of brief exposure or low pollution use respiratory filter device. In case of intensive or longe osure use respiratory protective device that is independent of circulating air. tection of hands:
Due	Protective gloves glove material has to be impermeable and resistant to the product/ the substance/ the preparation. to missing tests no recommendation to the glove material can be given for the product/ the
Sele degi	aration/ the chemical mixture. action of the glove material on consideration of the penetration times, rates of diffusion and th adation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 7)





Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 749 FULGURANT RED

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

Information on basic physical and General Information	
Appearance: Form: Color: Odor: Odor threshold:	Liquid Red Characteristic Not determined.
pH-value:	Not determined.
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 124 °C (255.2 °F)
Flash point:	27 °C (80.6 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	315 °C (599 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air vapor mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
Density at 20 °C (68 °F):	0.959 g/cm³ (8.00286 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.



(Contd. of page 6)

Printing date 09/11/2019

Reviewed on 06/28/2019

Page 8/13

Trade name: 749 FULGURANT RED

		(Contd. of page
 Solubility in / Miscibility with Water: 	Not miscible or difficult to mix.	
Waler.		
· Partition coefficient (n-octanol/v	vater): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	76.1 %	
Coating VOC content:	76.06 %	
Ū	729.4 g/l / 6.09 lb/gal	
Material VOC content:	729.4 g/l / 6.09 lb/gal	
Solids content:	23.9 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

· Primary irritant effect:

- on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.

(Contd. on page 9)

US

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 749 FULGURANT RED

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

· Carcinogenic categories

 IARC (International Agency for Research on Cancel

1330-20-7 xylene

100-41-4 ethylbenzene

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 10)

119

Page 9/13

(Contd. of page 8)

3

2B



Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 749 FULGURANT RED

(Contd. of page 9)

UN-Number DOT, ADR, IMDG, IATA	UN1263	
UN proper shipping name DOT ADR IMDG, IATA	Paint 1263 PAINT PAINT	
Transport hazard class(es)	.,	
DOT		
R MARTER F repr		
Class Label	3 Flammable liquids 3	
ADR, IMDG, IATA		
Class	3 Flammable liquids	
Label	3	
Packing group DOT, ADR, IMDG, IATA	<i>III</i>	
Environmental hazards: Marine pollutant:	No	
Special precautions for user EMS Number: Stowage Category	Warning: Flammable liquids F-E, <u>S-E</u> A	
<i>Transport in bulk according to Annex</i> <i>MARPOL73/78 and the IBC Code</i>	II of Not applicable.	
Transport/Additional information:		
DOT Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L	



Page 10/13

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 749 FULGURANT RED

	(Contd. of page 1
ADR	
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG · Limited quantities (LQ)	5L
 Excepted quantities (EQ) 	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 3	55 (extremely hazardous substances):				
None of th	None of the ingredients is listed.				
· Section 3	13 (Specific toxic chemical listings):				
1330-20-7	xylene				
100-41-4	ethylbenzene				
· TSCA (To	xic Substances Control Act):				
123-86-4	n-butyl acetate	ACTIVE			
9004-36-8	cellulose acetate butyrate	ACTIVE			
108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE			
1330-20-7	xylene	ACTIVE			
100-41-4	ethylbenzene	ACTIVE			
107-98-2	1-methoxy-2-propanol	ACTIVE			
· Hazardou	Hazardous Air Pollutants				
1330-20-7	xylene				
100-41-4	ethylbenzene				
· Propositio	on 65				
· Chemicals	s known to cause cancer:				
100-41-4	ethylbenzene				
· Chemicals	s known to cause reproductive toxicity for females:				
None of th	e ingredients is listed.				
· Chemicals	s known to cause reproductive toxicity for males:				
None of th	None of the ingredients is listed.				
<u> </u>		(Contd. on page 12)			



Page 11/13

Page 12/13

(Contd. of page 11)

D

A4

A3

Safety Data Sheet acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 749 FULGURANT RED

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

1330-20-7 xylene

100-41-4 ethylbenzene

· TLV (Threshold Limit Value established by ACGIH)

1330-20-7 xylene

100-41-4 ethylbenzene

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



- · Signal word Warning
- Hazard-determining components of labeling: n-butyl acetate
 Hazard statements Flammable liquid and vapor.
- Suspected of causing cancer.

May cause drowsiness or dizziness.

Precautionary statements
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF exposed or concerned: Get medical advice/attention.
Call a poison center/doctor if you feel unwell.

(Contd. on page 13)

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 749 FULGURANT RED

(Contd. of page 12)

Page 13/13

In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

<u>16 Other information</u>

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 09/11/2019 / -
- · Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 3: Flammable liquids - Category 3 Carc. 2: Carcinogenicity - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3



US -