



# Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

## 1 Identification

- **Product identifier**
- **Trade name: 767 PEARL BLUISH GREEN**
- **Article number: 767**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
General Paint Co. S.A.L.  
P.O. Box 7623  
Beirut  
LEBANON  
info@generalpaint.biz
- **Information department: Product Safety Department**
- **Emergency telephone number: 1-800-535-5053 contract number (89244)**

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

STOT RE2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

(Contd. on page 2)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

**Trade name: 767 PEARL BLUISH GREEN**

(Contd. of page 1)

**Signal word** Warning**Hazard-determining components of labeling:***n-butyl acetate**ethylbenzene***Hazard statements***Flammable liquid and vapor.**Suspected of causing cancer.**May cause drowsiness or dizziness.**May cause damage to the hearing organs through prolonged or repeated exposure.***Precautionary statements***Obtain special instructions before use.**Do not handle until all safety precautions have been read and understood.**Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**Ground/bond container and receiving equipment.**Use explosion-proof electrical/ventilating/lighting/equipment.**Use only non-sparking tools.**Take precautionary measures against static discharge.**Do not breathe dust/fume/gas/mist/vapors/spray.**Use only outdoors or in a well-ventilated area.**Wear protective gloves/protective clothing/eye protection/face protection.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**IF INHALED: Remove person to fresh air and keep comfortable for breathing.**IF exposed or concerned: Get medical advice/attention.**Call a poison center/doctor if you feel unwell.**Get medical advice/attention if you feel unwell.**In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.**Store in a well-ventilated place. Keep container tightly closed.**Store in a well-ventilated place. Keep cool.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.***Classification system:****NFPA ratings (scale 0 - 4)**

Health = 0

Fire = 3

Reactivity = 0

**HMIS-ratings (scale 0 - 4)**

Health = 0

Fire = 3

Reactivity = 0

**Other hazards****Results of PBT and vPvB assessment****PBT:** Not applicable.

(Contd. on page 3)

US



## Safety Data Sheet

### acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

**Trade name: 767 PEARL BLUISH GREEN**

· **vPvB:** Not applicable.

(Contd. of page 2)

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

|            |                                          |           |
|------------|------------------------------------------|-----------|
| 123-86-4   | n-butyl acetate                          | >50-≤100% |
| 1330-20-7  | xylene                                   | >2.5-≤10% |
| 64742-95-6 | Solvent naphtha (petroleum), light arom. | >2.5-≤10% |
| 100-41-4   | ethylbenzene                             | ≤2.5%     |

### 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Immediately remove any clothing soiled by the product.  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

US

(Contd. on page 4)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

**Trade name: 767 PEARL BLUISH GREEN**

(Contd. of page 3)

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

- **PAC-1:**

|            |                                 |                     |
|------------|---------------------------------|---------------------|
| 123-86-4   | n-butyl acetate                 | 5 ppm               |
| 1330-20-7  | xylene                          | 130 ppm             |
| 100-41-4   | ethylbenzene                    | 33 ppm              |
| 107-98-2   | 1-methoxy-2-propanol            | 100 ppm             |
| 108-65-6   | 2-methoxy-1-methylethyl acetate | 50 ppm              |
| 7664-38-2  | phosphoric acid                 | 3 mg/m <sup>3</sup> |
| 70657-70-4 | 2-methoxypropyl acetate         | 50 ppm              |

- **PAC-2:**

|            |                                 |                      |
|------------|---------------------------------|----------------------|
| 123-86-4   | n-butyl acetate                 | 200 ppm              |
| 1330-20-7  | xylene                          | 920* ppm             |
| 100-41-4   | ethylbenzene                    | 1100* ppm            |
| 107-98-2   | 1-methoxy-2-propanol            | 160 ppm              |
| 108-65-6   | 2-methoxy-1-methylethyl acetate | 1,000 ppm            |
| 7664-38-2  | phosphoric acid                 | 30 mg/m <sup>3</sup> |
| 70657-70-4 | 2-methoxypropyl acetate         | 1,000 ppm            |

- **PAC-3:**

|           |                                 |                       |
|-----------|---------------------------------|-----------------------|
| 123-86-4  | n-butyl acetate                 | 3000* ppm             |
| 1330-20-7 | xylene                          | 2500* ppm             |
| 100-41-4  | ethylbenzene                    | 1800* ppm             |
| 107-98-2  | 1-methoxy-2-propanol            | 660 ppm               |
| 108-65-6  | 2-methoxy-1-methylethyl acetate | 5000* ppm             |
| 7664-38-2 | phosphoric acid                 | 150 mg/m <sup>3</sup> |

(Contd. on page 5)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

**Trade name: 767 PEARL BLUISH GREEN**

(Contd. of page 4)

70657-70-4 2-methoxypropyl acetate

5,000 ppm

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
*Ensure good ventilation/exhaustion at the workplace.  
 Open and handle receptacle with care.  
 Prevent formation of aerosols.*
- **Information about protection against explosions and fires:**  
*Keep ignition sources away - Do not smoke.  
 Protect against electrostatic charges.  
 Keep respiratory protective device available.*
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** *No special requirements.*
- **Information about storage in one common storage facility:** *Not required.*
- **Further information about storage conditions:** *Keep receptacle tightly sealed.*
- **Storage class:** 3
- **Specific end use(s)** *No further relevant information available.*

### 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** *No further data; see item 7.*
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
*The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
 At this time, the remaining constituent has no known exposure limits.*

#### 123-86-4 n-butyl acetate

PEL Long-term value: 710 mg/m<sup>3</sup>, 150 ppm

REL Short-term value: 950 mg/m<sup>3</sup>, 200 ppm  
 Long-term value: 710 mg/m<sup>3</sup>, 150 ppm

TLV Short-term value: 712 mg/m<sup>3</sup>, 150 ppm  
 Long-term value: 238 mg/m<sup>3</sup>, 50 ppm

#### 1330-20-7 xylene

PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppm

REL Short-term value: 655 mg/m<sup>3</sup>, 150 ppm  
 Long-term value: 435 mg/m<sup>3</sup>, 100 ppm

TLV Short-term value: 651 mg/m<sup>3</sup>, 150 ppm  
 Long-term value: 434 mg/m<sup>3</sup>, 100 ppm  
 BEI

(Contd. on page 6)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

**Trade name: 767 PEARL BLUISH GREEN**

(Contd. of page 5)

### 100-41-4 ethylbenzene

|     |                                                                                                       |
|-----|-------------------------------------------------------------------------------------------------------|
| PEL | Long-term value: 435 mg/m <sup>3</sup> , 100 ppm                                                      |
| REL | Short-term value: 545 mg/m <sup>3</sup> , 125 ppm<br>Long-term value: 435 mg/m <sup>3</sup> , 100 ppm |
| TLV | Long-term value: 87 mg/m <sup>3</sup> , 20 ppm<br>BEI                                                 |

· **Ingredients with biological limit values:**

### 1330-20-7 xylene

|     |                                                                                              |
|-----|----------------------------------------------------------------------------------------------|
| BEI | 1.5 g/g creatinine<br>Medium: urine<br>Time: end of shift<br>Parameter: Methylhippuric acids |
|-----|----------------------------------------------------------------------------------------------|

### 100-41-4 ethylbenzene

|     |                                                                                                                                                                           |
|-----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| BEI | 0.7 g/g creatinine<br>Medium: urine<br>Time: end of shift at end of workweek<br>Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative) |
| -   | Medium: end-exhaled air<br>Time: not critical<br>Parameter: Ethyl benzene (semi-quantitative)                                                                             |

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 7)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

**Trade name: 767 PEARL BLUISH GREEN**

(Contd. of page 6)

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

### 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

**Form:** Liquid  
**Color:** BLUISH GREEN

- **Odor:** Characteristic
- **Odor threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

**Melting point/Melting range:** Undetermined.  
**Boiling point/Boiling range:** 120 °C (248 °F)

- **Flash point:** 27 °C (80.6 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** 370 °C (698 °F)

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

**Lower:** 1.2 Vol %  
**Upper:** 7.5 Vol %

- **Vapor pressure at 20 °C (68 °F):** 10.7 hPa (8 mm Hg)

(Contd. on page 8)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

**Trade name: 767 PEARL BLUISH GREEN**

(Contd. of page 7)

- |                                    |                                           |
|------------------------------------|-------------------------------------------|
| · <b>Density at 20 °C (68 °F):</b> | 0.984 g/cm <sup>3</sup> (8.21148 lbs/gal) |
| · <b>Relative density</b>          | Not determined.                           |
| · <b>Vapor density</b>             | Not determined.                           |
| · <b>Evaporation rate</b>          | Not determined.                           |

- |                                                  |                                   |
|--------------------------------------------------|-----------------------------------|
| · <b>Solubility in / Miscibility with Water:</b> | Not miscible or difficult to mix. |
|--------------------------------------------------|-----------------------------------|

- |                                                   |                 |
|---------------------------------------------------|-----------------|
| · <b>Partition coefficient (n-octanol/water):</b> | Not determined. |
|---------------------------------------------------|-----------------|

- |                     |                 |
|---------------------|-----------------|
| · <b>Viscosity:</b> |                 |
| <b>Dynamic:</b>     | Not determined. |
| <b>Kinematic:</b>   | Not determined. |

- |                              |                         |
|------------------------------|-------------------------|
| · <b>Solvent content:</b>    |                         |
| <b>Organic solvents:</b>     | 72.5 %                  |
| <b>Coating VOC content:</b>  | 72.55 %                 |
|                              | 713.9 g/l / 5.96 lb/gal |
| <b>Material VOC content:</b> | 713.9 g/l / 5.96 lb/gal |

- |                            |                                            |
|----------------------------|--------------------------------------------|
| <b>Solids content:</b>     | 27.4 %                                     |
| · <b>Other information</b> | No further relevant information available. |

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

#### 1330-20-7 xylene

|        |      |                      |
|--------|------|----------------------|
| Oral   | LD50 | 4,300 mg/kg (rat)    |
| Dermal | LD50 | 2,000 mg/kg (rabbit) |

(Contd. on page 9)

US





## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

**Trade name: 767 PEARL BLUISH GREEN**

(Contd. of page 8)

### 64742-95-6 Solvent naphtha (petroleum), light arom.

|            |          |                    |
|------------|----------|--------------------|
| Oral       | LD50     | >6,800 mg/kg (rat) |
| Dermal     | LD50     | >3,400 mg/kg (rab) |
| Inhalative | LC50/4 h | >10.2 mg/l (rat)   |

- **Primary irritant effect:**

- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

|           |              |    |
|-----------|--------------|----|
| 1330-20-7 | xylene       | 3  |
| 100-41-4  | ethylbenzene | 2B |

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

US

(Contd. on page 10)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019



**Trade name: 767 PEARL BLUISH GREEN**

(Contd. of page 9)

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- |                                       |                                                                                     |
|---------------------------------------|-------------------------------------------------------------------------------------|
| · <b>UN-Number</b>                    |                                                                                     |
| · <b>DOT, ADR, IMDG, IATA</b>         | UN1263                                                                              |
| · <b>UN proper shipping name</b>      |                                                                                     |
| · <b>DOT</b>                          | Paint                                                                               |
| · <b>ADR</b>                          | 1263 PAINT                                                                          |
| · <b>IMDG, IATA</b>                   | PAINT                                                                               |
| · <b>Transport hazard class(es)</b>   |                                                                                     |
| · <b>DOT</b>                          |                                                                                     |
|                                       |  |
| · <b>Class</b>                        | 3 Flammable liquids                                                                 |
| · <b>Label</b>                        | 3                                                                                   |
|                                       |                                                                                     |
| · <b>ADR, IMDG, IATA</b>              |                                                                                     |
|                                       |  |
| · <b>Class</b>                        | 3 Flammable liquids                                                                 |
| · <b>Label</b>                        | 3                                                                                   |
| · <b>Packing group</b>                |                                                                                     |
| · <b>DOT, ADR, IMDG, IATA</b>         | III                                                                                 |
| · <b>Environmental hazards:</b>       |                                                                                     |
| · <b>Marine pollutant:</b>            | No                                                                                  |
| · <b>Special precautions for user</b> | Warning: Flammable liquids                                                          |
| · <b>EMS Number:</b>                  | F-E, <u>S</u> -E                                                                    |

(Contd. on page 11)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

**Trade name: 767 PEARL BLUISH GREEN**

(Contd. of page 10)

|                                                                                  |                                                                                                                  |
|----------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|
| · <b>Stowage Category</b>                                                        | A                                                                                                                |
| · <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b> | Not applicable.                                                                                                  |
| · <b>Transport/Additional information:</b>                                       |                                                                                                                  |
| · <b>DOT</b>                                                                     |                                                                                                                  |
| · <b>Quantity limitations</b>                                                    | On passenger aircraft/rail: 60 L<br>On cargo aircraft only: 220 L                                                |
| -----                                                                            |                                                                                                                  |
| · <b>ADR</b>                                                                     |                                                                                                                  |
| · <b>Excepted quantities (EQ)</b>                                                | Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| -----                                                                            |                                                                                                                  |
| · <b>IMDG</b>                                                                    |                                                                                                                  |
| · <b>Limited quantities (LQ)</b>                                                 | 5L                                                                                                               |
| · <b>Excepted quantities (EQ)</b>                                                | Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| · <b>UN "Model Regulation":</b>                                                  | UN 1263 PAINT, 3, III                                                                                            |

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

|           |                 |
|-----------|-----------------|
| 1330-20-7 | xylene          |
| 100-41-4  | ethylbenzene    |
| 7664-38-2 | phosphoric acid |

· **TSCA (Toxic Substances Control Act):**

|           |                                 |        |
|-----------|---------------------------------|--------|
| 123-86-4  | n-butyl acetate                 | ACTIVE |
| 1330-20-7 | xylene                          | ACTIVE |
| 100-41-4  | ethylbenzene                    | ACTIVE |
| 107-98-2  | 1-methoxy-2-propanol            | ACTIVE |
| 108-65-6  | 2-methoxy-1-methylethyl acetate | ACTIVE |
| 7664-38-2 | phosphoric acid                 | ACTIVE |

· **Hazardous Air Pollutants**

|           |        |
|-----------|--------|
| 1330-20-7 | xylene |
|-----------|--------|

(Contd. on page 12)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

**Trade name: 767 PEARL BLUISH GREEN**

(Contd. of page 11)

|          |              |
|----------|--------------|
| 100-41-4 | ethylbenzene |
|----------|--------------|

· **Proposition 65**

· **Chemicals known to cause cancer:**

|          |              |
|----------|--------------|
| 100-41-4 | ethylbenzene |
|----------|--------------|

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

|           |        |  |   |
|-----------|--------|--|---|
| 1330-20-7 | xylene |  | I |
|-----------|--------|--|---|

|          |              |  |   |
|----------|--------------|--|---|
| 100-41-4 | ethylbenzene |  | D |
|----------|--------------|--|---|

· **TLV (Threshold Limit Value established by ACGIH)**

|           |        |  |    |
|-----------|--------|--|----|
| 1330-20-7 | xylene |  | A4 |
|-----------|--------|--|----|

|          |              |  |    |
|----------|--------------|--|----|
| 100-41-4 | ethylbenzene |  | A3 |
|----------|--------------|--|----|

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02   GHS07   GHS08

· **Signal word** Warning

· **Hazard-determining components of labeling:**

*n*-butyl acetate

ethylbenzene

· **Hazard statements**

Flammable liquid and vapor.

Suspected of causing cancer.

May cause drowsiness or dizziness.

May cause damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

(Contd. on page 13)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

**Trade name: 767 PEARL BLUISH GREEN**

(Contd. of page 12)

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Do not breathe dust/fume/gas/mist/vapors/spray.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/protective clothing/eye protection/face protection.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
IF exposed or concerned: Get medical advice/attention.  
Call a poison center/doctor if you feel unwell.  
Get medical advice/attention if you feel unwell.  
In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.  
Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.  
Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Product safety department
- **Contact:** N/A
- **Date of preparation / last revision** 09/11/2019 / -

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ICAO: International Civil Aviation Organisation  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
DOT: US Department of Transportation  
IATA: International Air Transport Association  
ACGIH: American Conference of Governmental Industrial Hygienists  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
HMS: Hazardous Materials Identification System (USA)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
NIOSH: National Institute for Occupational Safety  
OSHA: Occupational Safety & Health  
TLV: Threshold Limit Value  
PEL: Permissible Exposure Limit

(Contd. on page 14)



**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

**Trade name: 767 PEARL BLUISH GREEN**

(Contd. of page 13)

*REL: Recommended Exposure Limit*

*BEI: Biological Exposure Limit*

*Flam. Liq. 3: Flammable liquids – Category 3*

*Carc. 2: Carcinogenicity – Category 2*

*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*

*STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2*

US