



# Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

## 1 Identification

- **Product identifier**
- **Trade name: 771 GOLD DOME**
- **Article number: 771**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
General Paint Co. S.A.L.  
P.O. Box 7623  
Beirut  
LEBANON  
info@generalpaint.biz
- **Information department:** Product Safety Department
- **Emergency telephone number:** 1-800-535-5053 contract number (89244)

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**
- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

**Trade name: 771 GOLD DOME**

(Contd. of page 1)

**· Hazard pictograms**

GHS02 GHS07 GHS08

**· Signal word** *Danger***· Hazard-determining components of labeling:**

*n*-butyl acetate  
Naphtha (petroleum), hydrotreated heavy ethylbenzene

**· Hazard statements**

*Flammable liquid and vapor.*  
*Causes skin irritation.*  
*May cause genetic defects.*  
*May cause cancer.*  
*May cause drowsiness or dizziness.*  
*May cause damage to the hearing organs through prolonged or repeated exposure.*

**· Precautionary statements**

*Obtain special instructions before use.*  
*Do not handle until all safety precautions have been read and understood.*  
*Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*  
*Ground/bond container and receiving equipment.*  
*Use explosion-proof electrical/ventilating/lighting/equipment.*  
*Use only non-sparking tools.*  
*Take precautionary measures against static discharge.*  
*Do not breathe dust/fume/gas/mist/vapors/spray.*  
*Wash thoroughly after handling.*  
*Use only outdoors or in a well-ventilated area.*  
*Wear protective gloves/protective clothing/eye protection/face protection.*  
*If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*  
*IF INHALED: Remove person to fresh air and keep comfortable for breathing.*  
*IF exposed or concerned: Get medical advice/attention.*  
*Call a poison center/doctor if you feel unwell.*  
*Specific treatment (see on this label).*  
*Get medical advice/attention if you feel unwell.*  
*Take off contaminated clothing and wash it before reuse.*  
*If skin irritation occurs: Get medical advice/attention.*  
*In case of fire: Use for extinction: CO2, powder or water spray.*  
*Store in a well-ventilated place. Keep container tightly closed.*  
*Store in a well-ventilated place. Keep cool.*  
*Store locked up.*  
*Dispose of contents/container in accordance with local/regional/national/international regulations.*

(Contd. on page 3)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 771 GOLD DOME

(Contd. of page 2)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = *1
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

123-86-4	n-butyl acetate	>25-≤50%
1330-20-7	xylene	>10-≤25%
64742-95-6	Solvent naphtha (petroleum), light arom.	>2.5-≤10%
108-65-6	2-methoxy-1-methylethyl acetate	>2.5-≤10%
7429-90-5	aluminium powder (stabilised)	>2.5-≤10%
64742-48-9	Naphtha (petroleum), hydrotreated heavy	>2.5-≤10%
100-41-4	ethylbenzene	≤2.5%

### 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Immediately remove any clothing soiled by the product.  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.

(Contd. on page 4)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 771 GOLD DOME

(Contd. of page 3)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

123-86-4	n-butyl acetate	5 ppm
1330-20-7	xylene	130 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	350 mg/m <sup>3</sup>
100-41-4	ethylbenzene	33 ppm
107-98-2	1-methoxy-2-propanol	100 ppm
7664-38-2	phosphoric acid	3 mg/m <sup>3</sup>
70657-70-4	2-methoxypropyl acetate	50 ppm

(Contd. on page 5)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 771 GOLD DOME

(Contd. of page 4)

· PAC-2:		
123-86-4	<i>n</i> -butyl acetate	200 ppm
1330-20-7	xylene	920* ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	1,800 mg/m <sup>3</sup>
100-41-4	ethylbenzene	1100* ppm
107-98-2	1-methoxy-2-propanol	160 ppm
7664-38-2	phosphoric acid	30 mg/m <sup>3</sup>
70657-70-4	2-methoxypropyl acetate	1,000 ppm

· PAC-3:		
123-86-4	<i>n</i> -butyl acetate	3000* ppm
1330-20-7	xylene	2500* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
64742-48-9	Naphtha (petroleum), hydrotreated heavy	40,000 mg/m <sup>3</sup>
100-41-4	ethylbenzene	1800* ppm
107-98-2	1-methoxy-2-propanol	660 ppm
7664-38-2	phosphoric acid	150 mg/m <sup>3</sup>
70657-70-4	2-methoxypropyl acetate	5,000 ppm

### 7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

- **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:** No special requirements.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:** Keep receptacle tightly sealed.

- **Storage class:** 3

- **Specific end use(s)** No further relevant information available.

US

(Contd. on page 6)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 771 GOLD DOME

(Contd. of page 5)

### 8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

#### 123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
REL	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 712 mg/m <sup>3</sup> , 150 ppm Long-term value: 238 mg/m <sup>3</sup> , 50 ppm

#### 1330-20-7 xylene

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm BEI

#### 108-65-6 2-methoxy-1-methylethyl acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

#### 100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL	Short-term value: 545 mg/m <sup>3</sup> , 125 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 87 mg/m <sup>3</sup> , 20 ppm BEI

· **Ingredients with biological limit values:**

#### 1330-20-7 xylene

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

(Contd. on page 7)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

**Trade name: 771 GOLD DOME**

(Contd. of page 6)

**100-41-4 ethylbenzene**

BEI	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-	Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
  - Keep away from foodstuffs, beverages and feed.
  - Immediately remove all soiled and contaminated clothing.
  - Wash hands before breaks and at the end of work.
  - Store protective clothing separately.
  - Avoid contact with the skin.
  - Avoid contact with the eyes and skin.
- **Breathing equipment:**
  - In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 8)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 771 GOLD DOME

(Contd. of page 7)

· **Eye protection:**

Tightly sealed goggles

### 9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

· <b>Form:</b>	Liquid
· <b>Color:</b>	GOLD
· <b>Odor:</b>	Characteristic
· <b>Odor threshold:</b>	Not determined.

· **pH-value:** Not determined.· **Change in condition**

· <b>Melting point/Melting range:</b>	Undetermined.
· <b>Boiling point/Boiling range:</b>	124-128 °C (255.2-262.4 °F)

· **Flash point:** 27 °C (80.6 °F)· **Flammability (solid, gaseous):** Not applicable.· **Ignition temperature:** 315 °C (599 °F)· **Decomposition temperature:** Not determined.· **Auto igniting:** Product is not selfigniting.· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.· **Explosion limits:**

· <b>Lower:</b>	1.1 Vol %
· <b>Upper:</b>	7.5 Vol %

· **Vapor pressure at 20 °C (68 °F):** 10.7 hPa (8 mm Hg)· **Density at 20 °C (68 °F):** 0.984 g/cm<sup>3</sup> (8.21148 lbs/gal)· **Relative density** Not determined.· **Vapor density** Not determined.· **Evaporation rate** Not determined.· **Solubility in / Miscibility with**· **Water:** Not miscible or difficult to mix.· **Partition coefficient (n-octanol/water):** Not determined.

(Contd. on page 9)

US





## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 771 GOLD DOME

(Contd. of page 8)

- |                              |  |
|------------------------------|--|
| <b>· Viscosity:</b>          |  |
| <b>Dynamic:</b>              | Not determined.                            |
| <b>Kinematic:</b>            | Not determined.                            |
| <b>· Solvent content:</b>    |  |
| <b>Organic solvents:</b>     | 74.1 %                                     |
| <b>Coating VOC content:</b>  | 74.07 %                                    |
| <b>Material VOC content:</b> | 728.8 g/l / 6.08 lb/gal                    |
|                              | 728.8 g/l / 6.08 lb/gal                    |
| <b>Solids content:</b>       | 28.4 %                                     |
| <b>· Other information</b>   | No further relevant information available. |

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

#### 1330-20-7 xylene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

#### 64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.

(Contd. on page 10)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

**Trade name: 771 GOLD DOME**

(Contd. of page 9)

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

### 12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 11)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 771 GOLD DOME

(Contd. of page 10)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1263

- **UN proper shipping name**
- **DOT** Paint
- **ADR** 1263 PAINT
- **IMDG, IATA** PAINT

- **Transport hazard class(es)**
- **DOT**



- **Class** 3 Flammable liquids
- **Label** 3

- **ADR, IMDG, IATA**



- **Class** 3 Flammable liquids
- **Label** 3

- **Packing group**
- **DOT, ADR, IMDG, IATA** III

- **Environmental hazards:**
- **Marine pollutant:** No

- **Special precautions for user** Warning: Flammable liquids
- **EMS Number:** F-E,S-E
- **Stowage Category** A

- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

(Contd. on page 12)

US



## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 771 GOLD DOME

(Contd. of page 11)

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations**

On passenger aircraft/rail: 60 L  
On cargo aircraft only: 220 L

· **ADR**

· **Excepted quantities (EQ)**

Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml

· **IMDG**

· **Limited quantities (LQ)**

· **Excepted quantities (EQ)**

5L  
Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":**

UN 1263 PAINT, 3, III

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7 xylene

100-41-4 ethylbenzene

7664-38-2 phosphoric acid

· **TSCA (Toxic Substances Control Act):**

123-86-4 n-butyl acetate

ACTIVE

1330-20-7 xylene

ACTIVE

108-65-6 2-methoxy-1-methylethyl acetate

ACTIVE

64742-48-9 Naphtha (petroleum), hydrotreated heavy

ACTIVE

100-41-4 ethylbenzene

ACTIVE

107-98-2 1-methoxy-2-propanol

ACTIVE

7664-38-2 phosphoric acid

ACTIVE

· **Hazardous Air Pollutants**

1330-20-7 xylene

100-41-4 ethylbenzene

(Contd. on page 13)

us



## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 771 GOLD DOME

(Contd. of page 12)

- **Proposition 65**

- **Chemicals known to cause cancer:**

100-41-4	ethylbenzene
----------	--------------

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.	
------------------------------------	--

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.	
------------------------------------	--

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.	
------------------------------------	--

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
-----------	--------	---

100-41-4	ethylbenzene	D
----------	--------------	---

- **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7	xylene	A4
-----------	--------	----

100-41-4	ethylbenzene	A3
----------	--------------	----

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.	
------------------------------------	--

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

*n*-butyl acetate

Naphtha (petroleum), hydrotreated heavy

ethylbenzene

- **Hazard statements**

Flammable liquid and vapor.

Causes skin irritation.

May cause genetic defects.

May cause cancer.

May cause drowsiness or dizziness.

May cause damage to the hearing organs through prolonged or repeated exposure.

- **Precautionary statements**

Obtain special instructions before use.

(Contd. on page 14)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

**Trade name: 771 GOLD DOME**

(Contd. of page 13)

- Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting/equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Do not breathe dust/fume/gas/mist/vapors/spray.  
Wash thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/protective clothing/eye protection/face protection.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
IF exposed or concerned: Get medical advice/attention.  
Call a poison center/doctor if you feel unwell.  
Specific treatment (see on this label).  
Get medical advice/attention if you feel unwell.  
Take off contaminated clothing and wash it before reuse.  
If skin irritation occurs: Get medical advice/attention.  
In case of fire: Use for extinction: CO<sub>2</sub>, powder or water spray.  
Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.  
Dispose of contents/container in accordance with local/regional/national/international regulations.
- **National regulations:**
  - **Additional classification according to Decree on Hazardous Materials:**  
Carcinogenic hazardous material group III (dangerous).
  - **Information about limitation of use:**  
Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.
  - **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Product safety department
- **Contact:** N/A
- **Date of preparation / last revision** 09/11/2019 / -
- **Abbreviations and acronyms:**  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
DOT: US Department of Transportation  
IATA: International Air Transport Association  
ACGIH: American Conference of Governmental Industrial Hygienists  
EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 15)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

**Trade name: 771 GOLD DOME**

(Contd. of page 14)

*ELINCS: European List of Notified Chemical Substances*  
*CAS: Chemical Abstracts Service (division of the American Chemical Society)*  
*NFPA: National Fire Protection Association (USA)*  
*HMS: Hazardous Materials Identification System (USA)*  
*VOC: Volatile Organic Compounds (USA, EU)*  
*LC50: Lethal concentration, 50 percent*  
*LD50: Lethal dose, 50 percent*  
*PBT: Persistent, Bioaccumulative and Toxic*  
*vPvB: very Persistent and very Bioaccumulative*  
*NIOSH: National Institute for Occupational Safety*  
*OSHA: Occupational Safety & Health*  
*TLV: Threshold Limit Value*  
*PEL: Permissible Exposure Limit*  
*REL: Recommended Exposure Limit*  
*BEI: Biological Exposure Limit*  
*Flam. Liq. 3: Flammable liquids – Category 3*  
*Skin Irrit. 2: Skin corrosion/irritation – Category 2*  
*Muta. 1B: Germ cell mutagenicity – Category 1B*  
*Carc. 1B: Carcinogenicity – Category 1B*  
*STOT SE 3: Specific target organ toxicity (single exposure) – Category 3*  
*STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2*

US