
Printing date 09/11/2019

Reviewed on 06/28/2019

### 1 Identification

- · Product identifier
- · Trade name: <u>776 SPARKLE RED</u>
- · Article number: 776
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: General Paint Co. S.A.L. P.O. Box 7623 Beirut LEBANON info@generalpaint.biz
- Information department: Product Safety Department
   Emergency telephone number: 1-800-535-5053 contract number (89244)

#### 2 Hazard(s) identification





Printing date 09/11/2019

Reviewed on 06/28/2019

#### Trade name: 776 SPARKLE RED

(Contd. of page 1) · Hazard pictograms GHS02 GHS07 GHS08 · Signal word Warning Hazard-determining components of labeling: n-butyl acetate ethylbenzene · Hazard statements Flammable liquid and vapor. Causes skin irritation. Suspected of causing cancer. May cause drowsiness or dizziness. May cause damage to the hearing organs through prolonged or repeated exposure. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. (Contd. on page 3) US



Page 2/15

*Printing date 09/11/2019* 

Reviewed on 06/28/2019

### Trade name: 776 SPARKLE RED

Classification system:
 NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)



### · Other hazards

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

### 3 Composition/information on ingredients

### · Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
	n-butyl acetate	>25- <i>≤</i> 50%	
1330-20-7	-	>10- <i>≤</i> 25%	
64742-95-6	Solvent naphtha (petroleum), light arom.	>2.5- <i>≤</i> 10%	
108-65-6	2-methoxy-1-methylethyl acetate	<i>≤</i> 2.5%	
100-41-4	ethylbenzene	<i>≤</i> 2.5%	

### 4 First-aid measures

- · Description of first aid measures
- · General information:
- Immediately remove any clothing soiled by the product.
- Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- $\cdot$  Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 4)



(Contd. of page 2)



Printing date 09/11/2019

Reviewed on 06/28/2019

### Trade name: 776 SPARKLE RED

• Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

### 6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- Reference to other sections
   See Section 7 for information on safe handling.
   See Section 8 for information on personal protection equipment.
   See Section 13 for disposal information.
   Protective Action Criteria for Chemicale

### Protective Action Criteria for Chemicals

· PAC-1:		
123-86-4	n-butyl acetate	5 ppm
1330-20-7	xylene	130 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
100-41-4	ethylbenzene	33 ppm
107-98-2	107-98-2 1-methoxy-2-propanol	
	7664-38-2 phosphoric acid	
70657-70-4	70657-70-4 2-methoxypropyl acetate	
57-55-6	Propylene glycol	30 mg/m <sup>3</sup>
78-83-1	butanol	150 ppm
· PAC-2:		
123-86-4	n-butyl acetate	200 ppm
		(Contd. on page 5)



Page 4/15

(Contd. of page 3)

*Printing date 09/11/2019* 

Reviewed on 06/28/2019

### Trade name: 776 SPARKLE RED

		(Control of none 4)		
1330-20-7	xylene	(Contd. of page 4) 920* ppm		
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm		
100-41-4	ethylbenzene	1100* ppm		
107-98-2	1-methoxy-2-propanol	160 ppm		
7664-38-2	phosphoric acid	30 mg/m <sup>3</sup>		
70657-70-4	2-methoxypropyl acetate	1,000 ppm		
57-55-6	Propylene glycol	1,300 mg/m <sup>3</sup>		
78-83-1	butanol	1,300 ppm		
· PAC-3:	· PAC-3:			
123-86-4	n-butyl acetate	3000* ppm		
1330-20-7	xylene	2500* ppm		
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm		
100-41-4	ethylbenzene	1800* ppm		
107-98-2	1-methoxy-2-propanol	660 ppm		
7664-38-2	phosphoric acid	150 mg/m³		
70657-70-4	2-methoxypropyl acetate	5,000 ppm		
57-55-6	Propylene glycol	7,900 mg/m <sup>3</sup>		
78-83-1	butanol	8000* ppm		

### 7 Handling and storage

#### · Handling:

- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
   Open and handle receptacle with care.
   Prevent formation of aerosols.
   Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
- Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- Specific end use(s) No further relevant information available.

(Contd. on page 6)



Page 5/15

Printing date 09/11/2019

Reviewed on 06/28/2019

### Trade name: 776 SPARKLE RED

(Contd. of page 5)

8 Exposure controls/personal protection				
· Additional information about design of technical systems: No further data; see item 7.				
<ul> <li>Control parameters</li> <li>Components with limit values that require monitoring at the workplace: The following constituents are the only constituents of the product which have a PEL, TLV or othe recommended exposure limit. At this time, the remaining constituent has no known exposure limits.</li> </ul>				
123-86-4 n-butyl acetate				
PEL Long-term value: 710 mg/m <sup>3</sup> , 150 ppm				
REL Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm				
TLV Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm				
1330-20-7 xylene				
PEL Long-term value: 435 mg/m³, 100 ppm				
REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm				
TLV Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm BEI				
108-65-6 2-methoxy-1-methylethyl acetate				
WEEL Long-term value: 50 ppm				
100-41-4 ethylbenzene				
PEL Long-term value: 435 mg/m <sup>3</sup> , 100 ppm				
REL Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm				
TLV Long-term value: 87 mg/m <sup>3</sup> , 20 ppm BEI				
Ingredients with biological limit values:				
1330-20-7 xylene				
BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids				
(Contd. on page 7				



Page 6/15

Page 7/15

# Safety Data Sheet acc. to OSHA HCS

*Printing date 09/11/2019* 

Reviewed on 06/28/2019

### Trade name: 776 SPARKLE RED

	(Contd. of page 6)
100	-41-4 ethylbenzene
BEI	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative) - Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)
· Add	<b>litional information:</b> The lists that were valid during the creation were used as basis.
<ul> <li>Person</li> <li>Gen</li> <li>Kee</li> <li>Imm</li> <li>Was</li> <li>Stor</li> <li>Avo</li> <li>Avo</li> <li>Bre</li> <li>In c</li> <li>exposition</li> </ul>	posure controls sonal protective equipment: meral protective and hygienic measures: p away from foodstuffs, beverages and feed. mediately remove all soiled and contaminated clothing. sh hands before breaks and at the end of work. re protective clothing separately. wid contact with the skin. id contact with the skin. athing equipment: ase of brief exposure or low pollution use respiratory filter device. In case of intensive or longer osure use respiratory protective device that is independent of circulating air. tection of hands:
PHI .	Protective gloves
Due prep Sele deg	glove material has to be impermeable and resistant to the product/ the substance/ the preparation. to missing tests no recommendation to the glove material can be given for the product/ the paration/ the chemical mixture. ection of the glove material on consideration of the penetration times, rates of diffusion and the radation

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 8)

Printing date 09/11/2019

Reviewed on 06/28/2019

### Trade name: 776 SPARKLE RED

· Eye protection:

Tightly sealed goggles

### 9 Physical and chemical properties

Appearance:	
Form:	Liquid
Color:	Red Characteristic
Odor: Odor threshold:	Characteristic Not determined.
pH-value:	Not determined.
•	
Change in condition Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	124 °C (255.2 °F)
Flash point:	27 °C (80.6 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	370 °C (698 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive ail vapor mixtures are possible.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	7.5 Vol %
Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
Density at 20 °C (68 °F):	0.9692 g/cm³ (8.08797 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	er): Not determined.

Page 8/15

(Contd. of page 7)



Printing date 09/11/2019

Reviewed on 06/28/2019

### Trade name: 776 SPARKLE RED

		(Contd. of page 8
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	73.5 %	
Coating VOC content:	73.48 %	
Ū	712.2 g/l / 5.94 lb/gal	
Material VOC content:	712.2 g/l / 5.94 lb/gal	
Solids content:	26.5 %	
· Other information	No further relevant information available.	

### 10 Stability and reactivity

· Reactivity No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

LD/LC50 values that are relevant for classification:		
1330-20-7	xylene	
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
64742-95-	6 Solvent	naphtha (petroleum), light arom.
Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)
on the ey	<b>in:</b> Irritant : <b>e:</b> No irrita	to skin and mucous membranes.

(Contd. on page 10)



Page 10/15

(Contd. of page 9)

3 2B

# Safety Data Sheet acc. to OSHA HCS

*Printing date 09/11/2019* 

Reviewed on 06/28/2019

### Trade name: 776 SPARKLE RED

### · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: *Irritant* 

· Carcinogenic categories

### · IARC (International Agency for Research on Cancer)

1330-20-7 xylene

100-41-4 ethylbenzene

· NTP (National Toxicology Program)

None of the ingredients is listed.

### · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

### · Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

### · Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 11)

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 776 SPARKLE RED

Uncleaned packagings:
 Recommendation: Disposal must be made according to official regulations.

UN-Number	
DOT, ADR, IMDG, IATA	UN1263
UN proper shipping name	
DOT	Paint
ADR	1263 PAINT
IMDG, IATA	PAINT
Transport hazard class(es)	
DOT, IMDG, IATA	
Label	3
ADR	
Class	3 Flammable liquids
Label	3
Packing group	
DOT, ADR, IMDG, IATA	III
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
EMS Number:	F-E, <u>S-E</u>
Stowage Category	A
Transport in bulk according to Annex	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L



(Contd. of page 10)



Page 12/15

# Safety Data Sheet acc. to OSHA HCS

*Printing date 09/11/2019* 

ENERAL

Reviewed on 06/28/2019

Trade name: 776 SPARKLE RED

	(Contd. of page
ADR	
<ul> <li>Excepted quantities (EQ)</li> </ul>	Code: E1
••••	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· IMDG	
Limited quantities (LQ)	5L
· Excepted quantities (ÉQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

### 15 Regulatory information

 $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  Sara

Section 3	13 (Specific toxic chemical listings):	
1330-20-7	xylene	
100-41-4	ethylbenzene	
7664-38-2	phosphoric acid	
TSCA (To	xic Substances Control Act):	
123-86-4	n-butyl acetate	ACTIV
1330-20-7	xylene	ACTIV
9004-36-8	cellulose acetate butyrate	ACTIV
108-65-6	2-methoxy-1-methylethyl acetate	ACTIV
100-41-4	ethylbenzene	ACTIV
107-98-2	1-methoxy-2-propanol	ACTIV
7664-38-2	phosphoric acid	ACTIV
57-55-6	Propylene glycol	ACTIV
78-83-1	butanol	ACTIV
Hazardou	s Air Pollutants	
1330-20-7	xylene	
100-41-4	ethylbenzene	
Propositio	on 65	
Chemical	s known to cause cancer:	
100-41-4	ethylbenzene	

Page 13/15

(Contd. of page 12)

1

D

A4

AЗ

# Safety Data Sheet acc. to OSHA HCS

*Printing date 09/11/2019* 

Reviewed on 06/28/2019

### Trade name: 776 SPARKLE RED

 $\cdot$  Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

### · Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

#### Carcinogenic categories

· EPA (Environmental Protection Agency)

1330-20-7 xylene

100-41-4 ethylbenzene

### · TLV (Threshold Limit Value established by ACGIH)

1330-20-7 xylene

100-41-4 ethylbenzene

### · NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

### • GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



### · Signal word Warning

- · Hazard-determining components of labeling:
- n-butyl acetate ethylbenzene

· Hazard statements

Flammable liquid and vapor.

Causes skin irritation.

- Suspected of causing cancer.
- May cause drowsiness or dizziness.

May cause damage to the hearing organs through prolonged or repeated exposure.

# Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

(Contd. on page 14)

<sup>-</sup> US

Page 14/15

# Safety Data Sheet acc. to OSHA HCS

Printing date 09/11/2019

### Reviewed on 06/28/2019

### Trade name: 776 SPARKLE RED

	Contd. of page 13)
Take precautionary measures against static discharge.	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/	shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
IF exposed or concerned: Get medical advice/attention.	
Call a poison center/doctor if you feel unwell.	
Specific treatment (see on this label).	
Get medical advice/attention if you feel unwell.	
Take off contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
In case of fire: Use for extinction: CO2, powder or water spray.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international reg	ulations
Chemical safety assessment: A Chemical Safety Assessment has not been carried ou	

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product safety department

- · Contact: N/A
- · Date of preparation / last revision 09/11/2019 / -

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Printing date 09/11/2019

Reviewed on 06/28/2019

### Trade name: 776 SPARKLE RED

BEI: Biological Exposure Limit Flam. Liq. 3: Flammable liquids – Category 3 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2



Page 15/15

(Contd. of page 14)