Printing date 09/11/2019

Reviewed on 06/28/2019

1 Identification

- · Product identifier
- · Trade name: 873 XIRALLIC GOLD
- · Article number: 873
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: General Paint Co. S.A.L. P.O. Box 7623 Beirut LEBANON info@generalpaint.biz
- Information department: Product Safety Department
 Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

Classification of the substance or mixture
GHS02 Flame
Flam. Liq. 3 H226 Flammable liquid and vapor.
GHS08 Health hazard
Carc. 2 H351 Suspected of causing cancer.
STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.
GHS07
STOT SE 3 H336 May cause drowsiness or dizziness.
Label elements
GHS label elements
The product is classified and labeled according to the Globally Harmonized System (GHS).
Hazard pictograms
GHS02 GHS07 GHS08





US

Page 2/14

Safety Data Sheet acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 873 XIRALLIC GOLD

(Contd. of page 1)

· Signal word Warning · Hazard-determining components of labeling: n-butyl acetate ethylbenzene · Hazard statements Flammable liquid and vapor. Suspected of causing cancer. May cause drowsiness or dizziness. May cause damage to the hearing organs through prolonged or repeated exposure. · Precautionarv statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Get medical advice/attention if you feel unwell. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 0Fire = 3Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH 0 Health = 0FIRE 3 Fire = 3Reactivity = 0REACTIVITY 0 · Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. (Contd. on page 3)

Printing date 09/11/2019

Trade name: 873 XIRALLIC GOLD

· vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
	n-butyl acetate	>50- <i>≤</i> 100%	
1330-20-7		>2.5- <i>≤</i> 10%	
64742-95-6	Solvent naphtha (petroleum), light arom.	>2.5- <i>≤</i> 10%	
108-65-6	2-methoxy-1-methylethyl acetate	>2.5- <i>≤</i> 10%	
100-41-4	ethylbenzene	<i>≤</i> 2.5%	

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
 CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
 For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)



(Contd. of page 2)



Reviewed on 06/28/2019

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 873 XIRALLIC GOLD

· Advice for firefighters

· Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
 Mount respiratory protective device.
 Wear protective equipment Keep upprotected persons away
- Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.
- · Protective Action Criteria for Chemicals

PAC-1:		
123-86-4	n-butyl acetate	5 ppm
1330-20-7	xylene	130 ppr
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
100-41-4	ethylbenzene	33 ppm
107-98-2	1-methoxy-2-propanol	100 ppr
7664-38-2	phosphoric acid	3 mg/m
70657-70-4	2-methoxypropyl acetate	50 ppm
PAC-2:	·	<u>·</u>
123-86-4	n-butyl acetate	200 ppm
1330-20-7	xylene	920* ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppr
100-41-4	ethylbenzene	1100* ppr
107-98-2	1-methoxy-2-propanol	160 ppm
7664-38-2	phosphoric acid	30 mg/m ³
70657-70-4	2-methoxypropyl acetate	1,000 ppr
PAC-3:	·	
123-86-4	n-butyl acetate	3000* ppr
1330-20-7	xylene	2500* ppr
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppr
100-41-4	ethylbenzene	1800* ppr
(1-methoxy-2-propanol	660 ppm



CENERAL

(Contd. of page 3)

Page 4/14

US

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 873 XIRALLIC GOLD

7664-38-2 phosphoric acid

70657-70-4 2-methoxypropyl acetate

7 Handling and storage

· Handling:

- Precautions for safe handling
 Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

- · Control parameters
- Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

123-8	123-86-4 n-butyl acetate		
PEL	Long-term value: 710 mg/m ³ , 150 ppm		
REL	Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm		
TLV	Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm		
1330-2	1330-20-7 xylene		
PEL	Long-term value: 435 mg/m³, 100 ppm		
	(Contd. on page 6)		

US



Page 5/14

(Contd. of page 4)

 150 mg/m^3

5,000 ppm

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 873 XIRALLIC GOLD

	(Contd. of page
REL	
	Long-term value: 435 mg/m ³ , 100 ppm
TLV	
	Long-term value: 434 mg/m³, 100 ppm
400	BEI
	-65-6 2-methoxy-1-methylethyl acetate
	EL Long-term value: 50 ppm
	-41-4 ethylbenzene
PEL	
REL	0 / 11
	Long-term value: 435 mg/m³, 100 ppm
TLV	0 / 11
	BEI
-	edients with biological limit values:
	0-20-7 xylene
BEI	1.5 g/g creatinine
	Medium: urine
	Time: end of shift
	Parameter: Methylhippuric acids
	41-4 ethylbenzene
BEI	0.7 g/g creatinine
	Medium: urine
	Time: end of shift at end of workweek
	Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
	-
	Medium: end-exhaled air
	Time: not critical
	Parameter: Ethyl benzene (semi-quantitative)
· Add	itional information: The lists that were valid during the creation were used as basis.
	osure controls
	sonal protective equipment:
	eral protective and hygienic measures:
	p away from foodstuffs, beverages and feed.
	ediately remove all soiled and contaminated clothing.
Imm	
	h hands before breaks and at the end of work.
Was	h hands before breaks and at the end of work. e protective clothing separately.
Was Store	
Was Store • Brea In ca	e protective clothing separately.



Page 6/14

Page 7/14

(Contd. of page 6)

Safety Data Sheet acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 873 XIRALLIC GOLD

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

 Information on basic physical and General Information 	cnemical properties	
Appearance:		
Form:	Liquid	
Color:	Gold colored	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	120 °C (248 °F)	
Flash point:	27 °C (80.6 °F)	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	370 °C (698 °F)	

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 873 XIRALLIC GOLD

	(Contd. of page
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive ail vapor mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
Vapor pressure at 20 °C (68 °F):	10.7 hPa (8 mm Hg)
Density at 20 °C (68 °F):	0.963 g/cm³ (8.03624 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	74.3 %
Coating VOC content:	74.27 %
-	715.2 g/l / 5.97 lb/gal
Material VOC content:	715.2 g/l / 5.97 lb/gal
Solids content:	25.7 %
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

- No decomposition if used according to specifications. **Possibility of hazardous reactions** No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 9)

US



Page 8/14

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 873 XIRALLIC GOLD

(Contd. of page 8)

Page 9/14

	values tha	at are relevant for classification:
1330-20-7	' xylene	
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
64742-95-	6 Solvent	naphtha (petroleum), light arom.
Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)
on the ski on the eye Sensitizat Additiona	e: No irritat tion: No se I toxicolog	ant effect. ting effect. ensitizing effects known. gical information:
on the ski on the eye Sensitizat Additiona The produ preparatio	in: No irrita e: No irritat tion: No se Il toxicolog uct shows ns:	ant effect. ting effect. ensitizing effects known. gical information: the following dangers according to internally approved calculation methods
on the ski on the eye Sensitizat Additiona The produ preparatio Carcinoge	in: No irrita e: No irritat tion: No se al toxicolog uct shows ns: enic categ	ant effect. ting effect. ensitizing effects known. gical information: the following dangers according to internally approved calculation methods pories
on the ski on the eye Sensitizat Additiona The produ preparatio Carcinoge	in: No irrita e: No irrita tion: No se Il toxicolog uct shows ns: enic categ ernational	ant effect. ting effect. ensitizing effects known. gical information: the following dangers according to internally approved calculation methods
on the ski on the eye Sensitizat Additiona The produ preparatio Carcinoge IARC (Intel 1330-20-7	in: No irrita e: No irrita tion: No se Il toxicolog uct shows ns: enic categ ernational	ant effect. ting effect. ensitizing effects known. gical information: the following dangers according to internally approved calculation methods fories Agency for Research on Cancer)
on the ski on the eye Sensitizat Additiona The produ preparatio Carcinoge IARC (Intel 1330-20-7 100-41-4	in: No irrita e: No irrita tion: No se al toxicolog uct shows ns: enic categ ernational xylene ethylbenz	ant effect. ting effect. ensitizing effects known. gical information: the following dangers according to internally approved calculation methods fories Agency for Research on Cancer)

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

(Contd. on page 10)



US

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 873 XIRALLIC GOLD

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

UN-Number		
DOT, ADR, IMDG, IATA	UN1263	
UN proper shipping name		
DOT	Paint	
ADR	1263 PAINT	
IMDG, IATA	PAINT	
Transport hazard class(es)		
DOT		
PARAMETICAN 3		
Class	3 Flammable liquids	
Label	3	
ADR, IMDG, IATA		
Class	3 Flammable liquids	
Label	3	



Page 10/14

(Contd. of page 9)

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 873 XIRALLIC GOLD

	(Contd. of page 10)
 Packing group DOT, ADR, IMDG, IATA 	<i>III</i>
· Environmental hazards: · Marine pollutant:	No
 Special precautions for user EMS Number: Stowage Category 	Warning: Flammable liquids F-E,S-E A
 Transport in bulk according to Annex MARPOL73/78 and the IBC Code 	t II of Not applicable.
· Transport/Additional information:	
·DOT	
· Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
• ADR • Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):				
None of the ingredients is listed.				
· Section 313 (Specific toxic chemical listings):				
1330-20-7	xylene			
	ethylbenzene			
7664-38-2	phosphoric acid			
· TSCA (Tox	· TSCA (Toxic Substances Control Act):			
123-86-4	n-butyl acetate	ACTIVE		
1330-20-7	xylene	ACTIVE		
	(Contd.	on page 12)		





Page 12/14

Safety Data Sheet acc. to OSHA HCS

Printing date 09/11/2019

ENERAL

Reviewed on 06/28/2019

Trade name: 873 XIRALLIC GOLD

_		(Contd. of page 11)
	2-methoxy-1-methylethyl acetate	ACTIVE
	ethylbenzene	ACTIVE
	1-methoxy-2-propanol	ACTIVE
7664-38-2	phosphoric acid	ACTIVE
· Hazardou	s Air Pollutants	
1330-20-7	xylene	
100-41-4	ethylbenzene	
· Propositio	on 65	
· Chemicals	s known to cause cancer:	
100-41-4	ethylbenzene	
· Chemicals	s known to cause reproductive toxicity for females:	
None of th	e ingredients is listed.	
· Chemicals	s known to cause reproductive toxicity for males:	
None of th	e ingredients is listed.	
· Chemicals	s known to cause developmental toxicity:	
None of th	e ingredients is listed.	
· Carcinoge	enic categories	
-	ronmental Protection Agency)	
1330-20-7		1
100-41-4	ethylbenzene	D
· TLV (Thre	shold Limit Value established by ACGIH)	
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
· NIOSH-Ca	(National Institute for Occupational Safety and Health)	
None of th	e ingredients is listed.	
· GHS label	elements	
	ct is classified and labeled according to the Globally Harmonized System (Gl	1 S).
 Hazard pie 	ctograms	



· Signal word Warning

• *Hazard-determining components of labeling: n-butyl acetate ethylbenzene*

(Contd. on page 13)

US

Page 13/14

Safety Data Sheet acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 873 XIRALLIC GOLD

(Contd. of page 12) · Hazard statements Flammable liquid and vapor. Suspected of causing cancer. May cause drowsiness or dizziness. May cause damage to the hearing organs through prolonged or repeated exposure. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Get medical advice/attention if you feel unwell. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- Date of preparation / last revision 09/11/2019 / -
- Abbreviations and acronyms:
 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 ICAO: International Civil Aviation Organisation
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)

(Contd. on page 14)

⁻ US

Printing date 09/11/2019

ENERAL

Reviewed on 06/28/2019

Page 14/14

Trade name: 873 XIRALLIC GOLD

(Contd. of page 13) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent D50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPVB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 3: Flammable liquids – Category 3 Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 2

us -