Printing date 09/11/2019

Reviewed on 06/28/2019

1 Identification

- · Product identifier
- · Trade name: 718C REDDISH BLUE
- · Article number: 718C
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: General Paint Co. S.A.L. P.O. Box 7623 Beirut LEBANON info@generalpaint.biz
- Information department: Product Safety Department
 Emergency telephone number: 1-800-535-5053 contract number (89244)

2 Hazard(s) identification

· Classification of the substance or mixture GHS02 Flame Flam. Liq. 3 H226 Flammable liquid and vapor. GHS08 Health hazard H351 Suspected of causing cancer. Carc. 2 STOT RE2 H373 May cause damage to the hearing organs through prolonged or repeated exposure. GHS07 Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness. · Label elements · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2) US



Page 1/15

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 718C REDDISH BLUE

(Contd. of page 1) · Hazard pictograms GHS02 GHS07 GHS08 · Signal word Warning Hazard-determining components of labeling: methyl acetate ethylbenzene n-butyl acetate · Hazard statements Flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. May cause drowsiness or dizziness. May cause damage to the hearing organs through prolonged or repeated exposure. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eve protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsina. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. (Contd. on page 3)



Page 2/15

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 718C REDDISH BLUE

(Contd. of page 2) Dispose of contents/container in accordance with local/regional/national/international regulations. • Classification system:

· NFPA ratings (scale 0 - 4)

 $\begin{array}{c} \textbf{Health} = 2\\ \textbf{Fire} = 3\\ \textbf{Reactivity} = 0 \end{array}$

· HMIS-ratings (scale 0 - 4)

HEALTH2Health = 2FIRE3Fire = 3REACTIVITY0Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

 Dangerous 	· Dangerous components:		
79-20-9	methyl acetate	>25- <i>≤</i> 50%	
	4-chloro-alpha,alpha,alpha-trifluorotoluene	>25- <i>≤</i> 50%	
64742-95-6	Solvent naphtha (petroleum), light arom.	>2.5- <i>≤</i> 10%	
123-86-4	n-butyl acetate	>2.5- <i>≤</i> 10%	
1330-20-7	xylene	>2.5- <i>≤</i> 10%	
100-41-4	ethylbenzene	<i>≤</i> 2.5%	

4 First-aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation: In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • After swallowing: If symptoms persist consult doctor.

(Contd. on page 4)



Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 718C REDDISH BLUE

- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
79-20-9	methyl acetate	250 ppm
123-86-4	n-butyl acetate	5 ppm
1330-20-7	•	130 ppm
100-41-4	ethylbenzene	33 ppm
	2-methoxy-1-methylethyl acetate	50 ppm
107-98-2	1-methoxy-2-propanol	100 ppm
	2-butoxyethanol	60 ppm
70657-70-4	2-methoxypropyl acetate	50 ppm
		(Contd. on page 5)



(Contd. of page 3)



Printing date 09/11/2019

Reviewed on 06/28/2019

Page 5/15

Trade name: 718C REDDISH BLUE

PAC-2:		(Contd. of page
-	methyl acetate	1,700 ppm
123-86-4	n-butyl acetate	200 ppm
1330-20-7	xylene	920* ppm
100-41-4	ethylbenzene	1100* ppn
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
107-98-2	1-methoxy-2-propanol	160 ppm
111-76-2	2-butoxyethanol	120 ppm
70657-70-4	2-methoxypropyl acetate	1,000 ppm
PAC-3:		· · ·
79-20-9	methyl acetate	10000* ppn
123-86-4	n-butyl acetate	3000* ppm
1330-20-7	xylene	2500* ppm
100-41-4	ethylbenzene	1800* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
107-98-2	1-methoxy-2-propanol	660 ppm
111-76-2	2-butoxyethanol	700 ppm
70657-70-4	2-methoxypropyl acetate	5,000 ppm

7 Handling and storage

- · Handling:
- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
 Information about protection against explosions and fires:
- Keep ignition sources away Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- Storage class: 3
- · Specific end use(s) No further relevant information available.

(Contd. on page 6)



Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 718C REDDISH BLUE

(Contd. of page 5)

 Additional information about design of technical systems: No further data; see item 7. Control parameters Components with limit values that require monitoring at the workplace: The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits. 79-20-9 methyl acetate PEL Long-term value: 610 mg/m³, 200 ppm Short-term value: 610 mg/m³, 200 ppm Long-term value: 757 mg/m³, 250 ppm Long-term value: 757 mg/m³, 200 ppm Long-term value: 606 mg/m³, 200 ppm Long-term value: 750 mg/m³, 200 ppm Long-term value: 750 mg/m³, 200 ppm Long-term value: 750 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm REL Short-term value: 950 mg/m³, 150 ppm Long-term value: 710 mg/m³, 150 ppm Long-term value: 710 mg/m³, 150 ppm Long-term value: 238 mg/m³, 150 ppm Long-term value: 358 mg/m³, 150 ppm Long-term value: 655 mg/m³, 100 ppm Long-term value: 435 mg/m³, 100 ppm BEI 100-41-4 ethylbenzene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 435 mg/m³, 100 ppm TV V Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 435 mg/m³, 20 ppm BEI S	8 Exp	osure controls/personal protection
 Components with limit values that require monitoring at the workplace: The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits. 79-20-9 methyl acetate Long-term value: 610 mg/m³, 200 ppm REL Short-term value: 610 mg/m³, 200 ppm Long-term value: 606 mg/m³, 200 ppm 123-86-4 n-butyl acetate PEL Long-term value: 710 mg/m³, 150 ppm 123-86-4 n-butyl acetate PEL Long-term value: 710 mg/m³, 150 ppm 123-86-4 n-butyl acetate PEL Long-term value: 710 mg/m³, 150 ppm Long-term value: 710 mg/m³, 150 ppm Long-term value: 238 mg/m³, 150 ppm Long-term value: 435 mg/m³, 150 ppm Long-term value: 655 mg/m³, 150 ppm Long-term value: 651 mg/m³, 150 ppm Long-term value: 651 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 435 mg/m³, 100 ppm Long-term value: 435 mg/m³, 100 ppm EI 100-41-4 ethylbenzene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm EI 100-41-4 ethylbenze	· Addi	tional information about design of technical systems: No further data; see item 7.
 Components with limit values that require monitoring at the workplace: The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits. 79-20-9 methyl acetate Long-term value: 610 mg/m³, 200 ppm REL Short-term value: 610 mg/m³, 200 ppm Long-term value: 606 mg/m³, 200 ppm 123-86-4 n-butyl acetate PEL Long-term value: 710 mg/m³, 150 ppm 123-86-4 n-butyl acetate PEL Long-term value: 710 mg/m³, 150 ppm 123-86-4 n-butyl acetate PEL Long-term value: 710 mg/m³, 150 ppm Long-term value: 710 mg/m³, 150 ppm Long-term value: 238 mg/m³, 150 ppm Long-term value: 435 mg/m³, 150 ppm Long-term value: 655 mg/m³, 150 ppm Long-term value: 651 mg/m³, 150 ppm Long-term value: 651 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 435 mg/m³, 100 ppm Long-term value: 435 mg/m³, 100 ppm EI 100-41-4 ethylbenzene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm EI 100-41-4 ethylbenze	· Conf	rol parameters
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits. 79-20-9 methyl acetate PEL Long-term value: 610 mg/m³, 200 ppm REL Short-term value: 760 mg/m³, 200 ppm Long-term value: 610 mg/m³, 200 ppm Long-term value: 757 mg/m³, 250 ppm Long-term value: 606 mg/m³, 200 ppm 123-86-4 n-butyl acetate PEL Long-term value: 710 mg/m³, 150 ppm REL Short-term value: 710 mg/m³, 150 ppm Long-term value: 712 mg/m³, 150 ppm Long-term value: 728 mg/m³, 100 ppm PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 435 mg/m³, 100 ppm Long-term value: 435 mg/m³, 100 ppm BEI 100-41-4 ethylbenzene PEL Long-		
At this time, the other constituents have no known exposure limits. 79-20-9 methyl acetate PEL Long-term value: 610 mg/m³, 200 ppm Long-term value: 610 mg/m³, 250 ppm Long-term value: 757 mg/m³, 250 ppm Long-term value: 757 mg/m³, 250 ppm Long-term value: 606 mg/m³, 200 ppm 123-86-4 n-butyl acetate PEL PEL Long-term value: 710 mg/m³, 150 ppm Long-term value: 710 mg/m³, 150 ppm Long-term value: 710 mg/m³, 150 ppm Long-term value: 710 mg/m³, 150 ppm Long-term value: 712 mg/m³, 150 ppm Long-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 150 ppm Long-term value: 238 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 435 mg/m³, 100 ppm REL Short-term value: 435 mg/m³, 100 ppm Long-term value: 434 mg/m³, 100 ppm REL Short-term value: 435 mg/m³, 100 ppm Long-term value: 435 mg/m³, 100 ppm Long-term value: 435 mg/m³, 100 ppm Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 125 ppm Long-term value: 67 mg/m³, 20 ppm <t< th=""><th>The i</th><th>ollowing constituents are the only constituents of the product which have a PEL, TLV or other</th></t<>	The i	ollowing constituents are the only constituents of the product which have a PEL, TLV or other
T9-20-9 methyl acetate PEL Long-term value: 610 mg/m³, 200 ppm REL Short-term value: 760 mg/m³, 250 ppm Long-term value: 610 mg/m³, 200 ppm Long-term value: 610 mg/m³, 250 ppm Long-term value: 757 mg/m³, 250 ppm Long-term value: 757 mg/m³, 250 ppm Long-term value: 757 mg/m³, 250 ppm Long-term value: 70 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm REL Short-term value: 710 mg/m³, 150 ppm Long-term value: 710 mg/m³, 150 ppm Long-term value: 712 mg/m³, 150 ppm Long-term value: 712 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm PEL Nort-term value: 655 mg/m³, 100 ppm Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 435 mg/m³, 100 ppm BEI 100-41-4 ethylbenzene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 435 mg/m³, 100 ppm REL Short-term value: 435 mg/m³, 100 ppm BEI Long-term value: 435 mg/m³, 100 ppm BEI Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 435 mg/m³, 100 ppm BEI Long-term value: 435 mg/m³, 100 ppm BEI		
PEL Long-term value: 610 mg/m³, 200 ppm REL Short-term value: 610 mg/m³, 250 ppm Long-term value: 610 mg/m³, 250 ppm Long-term value: 606 mg/m³, 250 ppm Long-term value: 606 mg/m³, 250 ppm Long-term value: 606 mg/m³, 200 ppm 123-86-4 n-butyl acetate PEL PEL Long-term value: 710 mg/m³, 150 ppm REL Short-term value: 710 mg/m³, 150 ppm Long-term value: 710 mg/m³, 150 ppm Long-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 150 ppm Long-term value: 435 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 651 mg/m³, 150 ppm Long-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm BEI 100-41-4 ethylbenzene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 87 mg/m³, 20 ppm BEI 1010-14-14 ethylbenzene 1011-14 ethylbenzene 10111-14 ethylbenzene 		
REL Short-term value: 760 mg/m³, 250 ppm Long-term value: 610 mg/m³, 200 ppm TLV Short-term value: 757 mg/m³, 250 ppm Long-term value: 606 mg/m³, 200 ppm 123-86-4 n-butyl acetate PEL Long-term value: 710 mg/m³, 150 ppm REL Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm TV Short-term value: 712 mg/m³, 150 ppm Long-term value: 713 mg/m³, 150 ppm TUV Short-term value: 435 mg/m³, 100 ppm 1330-20-7 xylene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 651 mg/m³, 150 ppm Long-term value: 655 mg/m³, 100 ppm FEL Long-term value: 651 mg/m³, 100 ppm REL Short-term value: 651 mg/m³, 100 ppm BEI Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 651 mg/m³, 100 ppm REL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 100 ppm Long-term value: 87 mg/m³, 20 ppm Long-term value: 87 mg/m³, 20 ppm BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids (Contd. on page 7)		•
Long-term value: 610 mg/m³, 200 ppm TLV Short-term value: 757 mg/m³, 250 ppm Long-term value: 606 mg/m³, 200 ppm 123-86-4 n-butyl acetate PEL Long-term value: 950 mg/m³, 200 ppm Long-term value: 950 mg/m³, 200 ppm Long-term value: 950 mg/m³, 200 ppm Long-term value: 712 mg/m³, 150 ppm Long-term value: 728 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 100 ppm Long-term value: 655 mg/m³, 100 ppm REL Short-term value: 651 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 435 mg/m³, 100 ppm REL Short-term value: 435 mg/m³, 100 ppm BEI 100-41-4 ethylbenzene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term valu	PEL	Long-term value: 610 mg/m ³ , 200 ppm
TLV Short-term value: 757 mg/m³, 250 ppm Long-term value: 606 mg/m³, 200 ppm 123-86-4 n-butyl acetate PEL Long-term value: 710 mg/m³, 150 ppm Long-term value: 710 mg/m³, 150 ppm REL Short-term value: 710 mg/m³, 150 ppm Long-term value: 710 mg/m³, 150 ppm 130-20-7 xylene PEL PEL Long-term value: 435 mg/m³, 100 ppm Long-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm 130-20-7 xylene PEL PEL Long-term value: 435 mg/m³, 100 ppm Long-term value: 435 mg/m³, 100 ppm BEI 100-41-4 ethylbenzene PEL Long-term value: 435 mg/m³, 100 ppm BEI 100-41-4 ethylbenzene PEL Long-term value: 435 mg/m³, 100 ppm BEI 100-41-4 ethylbenzene PEL Long-term value: 435 mg/m³, 100 ppm BEI 100-41-4 ethylbenzene PEL Long-term value: 545 mg/m³, 125 ppm Long-term value: 87 mg/m³, 20 ppm BEI 11x Long-term value: 87 mg/m³, 20 ppm BEI Ingredients with biological limit values: 1330-20-7 xylene BEI BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids	REL	
Long-term value: 606 mğ/m³, 200 ppm 123-86-4 n-butyl acetate PEL Long-term value: 710 mg/m³, 150 ppm REL Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm Long-term value: 710 mg/m³, 150 ppm Long-term value: 712 mg/m³, 150 ppm Long-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm 133U-20-7 xylene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 651 mg/m³, 150 ppm Long-term value: 651 mg/m³, 150 ppm Long-term value: 651 mg/m³, 100 ppm BEI 100-41-4 ethylbenzene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 435 mg/m³, 100 ppm REL Short-term value: 435 mg/m³, 100 ppm REL Short-term value: 87 mg/m³, 20 ppm BEI Long-term value: 87 mg/m³, 20 ppm BEI Instrume value: 87 mg/m³, 20 ppm BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids (C		Long-term value: 610 mg/m ³ , 200 ppm
123-86-4 n-butyl acetate PEL Long-term value: 710 mg/m³, 150 ppm REL Short-term value: 710 mg/m³, 150 ppm Long-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm 1330-20-7 xylene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 655 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 655 mg/m³, 150 ppm Long-term value: 655 mg/m³, 100 ppm REL Short-term value: 651 mg/m³, 100 ppm BEI Long-term value: 435 mg/m³, 100 ppm BEI Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 435 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 100 ppm REL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 20 ppm BEI Long-term value: 87 mg/m³, 20 ppm BEI 1.5 g/g creatinine Medium: urine Medium: urine Time: end of shift Parameter: Methylhippuric acids<	TLV	
PEL Long-term value: 710 mg/m³, 150 ppm REL Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm Long-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm 1330-20-7 xylene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 6455 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 6435 mg/m³, 100 ppm REL Short-term value: 651 mg/m³, 100 ppm BEI Long-term value: 435 mg/m³, 100 ppm BEI Long-term value: 435 mg/m³, 100 ppm BEI Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 100 ppm REL Short-term value: 645 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 100 ppm BEI Long-term value: 87 mg/m³, 20 ppm BEI 1.5 g/g creatinine Medium: urine Medium: urine Time: end of shift Parameter: Methylhippuric acids		Long-term value: 606 mg/m³, 200 ppm
REL Short-term value: 950 mg/m³, 200 ppm Long-term value: 710 mg/m³, 150 ppm TLV Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm 1330-20-7 xylene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 655 mg/m³, 100 ppm TLV Short-term value: 651 mg/m³, 100 ppm BEI Long-term value: 434 mg/m³, 100 ppm BEI Long-term value: 435 mg/m³, 100 ppm BEI Long-term value: 435 mg/m³, 100 ppm BEI Long-term value: 435 mg/m³, 100 ppm BEI Short-term value: 435 mg/m³, 100 ppm BEI Short-term value: 435 mg/m³, 100 ppm REL Short-term value: 435 mg/m³, 100 ppm BEI Long-term value: 435 mg/m³, 100 ppm BEI Short-term value: 87 mg/m³, 20 ppm BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids Kettur: urine Time: end of shift Contd. on page 7)	123-8	36-4 n-butyl acetate
Long-term value: 710 mg/m³, 150 ppm TLV Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm 1330-20-7 xylene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 655 mg/m³, 100 ppm Long-term value: 651 mg/m³, 100 ppm Long-term value: 651 mg/m³, 100 ppm BEI 100-41-4 ethylbenzene PEL Long-term value: 435 mg/m³, 100 ppm BEI 100-41-4 ethylbenzene PEL Long-term value: 435 mg/m³, 100 ppm BEI 100-41-4 ethylbenzene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 125 ppm Long-term value: 87 mg/m³, 20 ppm BEI *Ingredients with biological limit values: 1330-20-7 xylene BEI BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids (Contd. on page 7)	PEL	Long-term value: 710 mg/m³, 150 ppm
TLV Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm 1330-20-7 xylene PEL Long-term value: 435 mg/m³, 100 ppm Long-term value: 655 mg/m³, 150 ppm Long-term value: 651 mg/m³, 100 ppm TLV Short-term value: 651 mg/m³, 100 ppm BEl 100-41-4 ethylbenzene PEL Long-term value: 435 mg/m³, 100 ppm BEl 100-41-4 ethylbenzene PEL Long-term value: 545 mg/m³, 100 ppm BEl 100-41-4 ethylbenzene PEL Long-term value: 545 mg/m³, 100 ppm BEl 100-41-4 ethylbenzene PEL Long-term value: 545 mg/m³, 100 ppm BEl 100-50-7 tylene BEI Short-term value: 87 mg/m³, 20 ppm BEl • Ingredients with biological limit values: 1330-20-7 xylene BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids (Contd. on page 7)	REL	Short-term value: 950 mg/m³, 200 ppm
Long-term value: 238 mg/m³, 50 ppm 1330-20-7 xylene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm TLV Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI 100-41-4 ethylbenzene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 100 ppm REL Short-term value: 435 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 100 ppm BEI Long-term value: 435 mg/m³, 100 ppm BEI Short-term value: 87 mg/m³, 20 ppm BEI 1.5 g/g creatinine Medium: urine Medium: urine Time: end of shift Parameter: Methylhippuric acids (Contd. on page 7)		Long-term value: 710 mg/m ³ , 150 ppm
1330-20-7 xylene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 651 mg/m³, 100 ppm TLV Short-term value: 651 mg/m³, 100 ppm BEI Long-term value: 434 mg/m³, 100 ppm BEI IO0-41-4 ethylbenzene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 100 ppm REL Short-term value: 435 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 100 ppm BEI Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 100 ppm BEI Long-term value: 87 mg/m³, 20 ppm BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids (Contd. on page 7)	TLV	Short-term value: 712 mg/m³, 150 ppm
PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 100 ppm Long-term value: 435 mg/m³, 100 ppm TLV Short-term value: 651 mg/m³, 100 ppm BEI Long-term value: 434 mg/m³, 100 ppm BEI Long-term value: 435 mg/m³, 100 ppm PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 100 ppm REL Short-term value: 435 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 100 ppm BEI Long-term value: 87 mg/m³, 20 ppm BEI Stort-term value: 87 mg/m³, 20 ppm BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids (Contd. on page 7)		Long-term value: 238 mg/m ³ , 50 ppm
REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 651 mg/m³, 150 ppm Long-term value: 651 mg/m³, 150 ppm BEI 100-41-4 ethylbenzene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 100 ppm REL Short-term value: 435 mg/m³, 100 ppm REL Short-term value: 435 mg/m³, 100 ppm Long-term value: 435 mg/m³, 100 ppm TLV Long-term value: 87 mg/m³, 20 ppm BEI • Ingredients with biological limit values: 1330-20-7 xylene BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids (Contd. on page 7)	1330	-20-7 xylene
Long-term value: 435 mg/m³, 100 ppm TLV Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI 100-41-4 ethylbenzene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm TLV Long-term value: 87 mg/m³, 20 ppm BEI · Ingredients with biological limit values: 1330-20-7 xylene BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids (Contd. on page 7)	PEL	Long-term value: 435 mg/m³, 100 ppm
TLV Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI 100-41-4 ethylbenzene PEL Long-term value: 435 mg/m³, 100 ppm Long-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm TLV Long-term value: 87 mg/m³, 20 ppm BEI • Ingredients with biological limit values: 1330-20-7 xylene BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids (Contd. on page 7)	REL	Short-term value: 655 mg/m³, 150 ppm
Long-term value: 434 mg/m³, 100 ppm BEI 100-41-4 ethylbenzene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm TLV Long-term value: 87 mg/m³, 20 ppm BEI · Ingredients with biological limit values: 1330-20-7 xylene BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids (Contd. on page 7)		Long-term value: 435 mg/m³, 100 ppm
BEI 100-41-4 ethylbenzene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm TLV Long-term value: 87 mg/m³, 20 ppm BEI • Ingredients with biological limit values: 130-20-7 xylene BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids (Contd. on page 7)	TLV	
100-41-4 ethylbenzene PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm TLV Long-term value: 87 mg/m³, 20 ppm BEI • Ingredients with biological limit values: 130-20-7 xylene BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids (Contd. on page 7)		
PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm TLV Long-term value: 87 mg/m³, 20 ppm BEI • Ingredients with biological limit values: 1330-20-7 xylene BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids (Contd. on page 7)		
REL Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm TLV Long-term value: 87 mg/m³, 20 ppm BEI • Ingredients with biological limit values: 1330-20-7 xylene BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids (Contd. on page 7)		•
Long-term value: 435 mg/m³, 100 ppm TLV Long-term value: 87 mg/m³, 20 ppm BEI . · Ingredients with biological limit values: 1330-20-7 xylene BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids (Contd. on page 7)		
TLV Long-term value: 87 mg/m³, 20 ppm BEI • Ingredients with biological limit values: 1330-20-7 xylene BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids (Contd. on page 7)	REL	
BEI • Ingredients with biological limit values: 1330-20-7 xylene BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids (Contd. on page 7)		Long-term value: 435 mg/m³, 100 ppm
 Ingredients with biological limit values: 1330-20-7 xylene BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids (Contd. on page 7) 	TLV	
1330-20-7 xylene BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids (Contd. on page 7)		BEI
BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids (Contd. on page 7)	· Ingre	dients with biological limit values:
Medium: urine Time: end of shift Parameter: Methylhippuric acids (Contd. on page 7)	1330	-20-7 xylene
Time: end of shift Parameter: Methylhippuric acids (Contd. on page 7)	BEI	1.5 g/g creatinine
Parameter: Methylhippuric acids (Contd. on page 7)		
(Contd. on page 7)		
		(Contd. on page 7)



Page 6/15

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 718C REDDISH BLUE

100-41-4 ethylbenzene

BEI 0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

· Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin.
- · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 8)

US



(Contd. of page 6)

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 718C REDDISH BLUE

· Eye protection:

Tightly sealed goggles

9 Physical and chemical properties

		neral Information pearance:
	Liquid	orm:
	Light blue	olor:
	Characteristic	or:
	Not determined.	or threshold:
	Not determined.	-value:
		ange in condition
	Undetermined.	lelting point/Melting range:
	57 °C (134.6 °F)	oiling point/Boiling range:
	27 °C (80.6 °F)	sh point:
	Not applicable.	mmability (solid, gaseous):
	455 °C (851 °F)	ition temperature:
	Not determined.	composition temperature:
	Product is not selfigniting.	to igniting:
of explosive air	Product is not explosive. However, formation of ex vapor mixtures are possible.	nger of explosion:
		plosion limits:
	3.1 Vol %	ower:
	16 Vol %	pper:
	220 hPa (165 mm Hg)	oor pressure at 20 °C (68 °F):
	1.079 g/cm³ (9.00426 lbs/gal)	nsity at 20 °C (68 °F):
	Not determined.	lative density
	Not determined.	por density
	Not determined.	aporation rate
		ubility in / Miscibility with
	Not miscible or difficult to mix.	later:
	r): Not determined.	rtition coefficient (n-octanol/wate
(Co	r): Not determined.	Vater:

Page 8/15

(Contd. of page 7)



Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 718C REDDISH BLUE

		(Contd. of page 8
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	75.8 %	
Coating VOC content:	15.97 %	
U U	419.2 g/l / 3.50 lb/gal	
Material VOC content:	172.3 g/l / 1.44 lb/gal	
Solids content:	24.2 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classified	cation:
---	---------

64742-95-		naphtha (petroleum), light arom.
Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>6,800 mg/kg (rat) >3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

· Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

(Contd. on page 10)



Page 9/15

US

Page 10/15

(Contd. of page 9)

3

2B 3

Safety Data Sheet acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 718C REDDISH BLUE

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

1330-20-7 xylene

100-41-4 ethylbenzene

111-76-2 2-butoxyethanol

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

2 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- Recommendation:
 Must not be disposed of together with house

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

(Contd. on page 11)

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 718C REDDISH BLUE

(Contd. of page 10)

nint 263 PAINT, ENVIRONMENTALLY HAZARDOUS AINT Flammable liquids
263 PAINT, ENVIRONMENTALLY HAZARDOUS AINT
263 PAINT, ENVIRONMENTALLY HAZARDOUS AINT
AINT
Flammable liquids
r iammable liquius
Flammable liquids
0
/arning: Flammable liquids
-E, <u>S-E</u>
a transferra to ta
ot applicable.
n passenger aircraft/rail: 60 L n cargo aircraft only: 220 L



Page 11/15

Printing date 09/11/2019

Reviewed on 06/28/2019

Page 12/15

Trade name: 718C REDDISH BLUE

	(Contd. of page 11
 ADR Excepted quantities (EQ) 	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture
Sara

None of the	e ingredients is listed.	
Section 31	3 (Specific toxic chemical listings):	
1330-20-7	xylene	
100-41-4	ethylbenzene	
111-76-2	2-butoxyethanol	
TSCA (To	kic Substances Control Act):	
79-20-9	methyl acetate	ACTIV
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	ACTIV
9004-36-8	cellulose acetate butyrate	ACTIV
123-86-4	n-butyl acetate	ACTIV
1330-20-7	xylene	ACTIV
100-41-4	ethylbenzene	ACTIV
108-65-6	2-methoxy-1-methylethyl acetate	ACTIV
107-98-2	1-methoxy-2-propanol	ACTIV
111-76-2	2-butoxyethanol	ACTIV
Hazardous	s Air Pollutants	
1330-20-7	xylene	
100-41-4	ethylbenzene	



Page 13/15

(Contd. of page 12)

Safety Data Sheet acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 718C REDDISH BLUE

· Proposition 65

· Chemicals known to cause cancer:

100-41-4 ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)			
1330-20-7		1	
	ethylbenzene	D	
111-76-2	2-butoxyethanol	NL	
· TLV (Threshold Limit Value established by ACGIH)			
1330-20-7		A4	
	ethylbenzene	A3	
111-76-2	2-butoxyethanol	А3	
NICOLL Co. (Notice not Institute for Coordinate Cofety and Uselik)			

• NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



· Signal word Warning

 Hazard-determining components of labeling: methyl acetate ethylbenzene n-butyl acetate Hazard statements

Flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. May cause drowsiness or dizziness.

(Contd. on page 14)

US

Page 14/15

Safety Data Sheet acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 718C REDDISH BLUE

(Contd. of page 13) May cause damage to the hearing organs through prolonged or repeated exposure. Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 09/11/2019 / -
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

(Contd. on page 15)

US

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 718C REDDISH BLUE

DEL: Dormissible Exposure Limit	
PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value	
NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value	
OSHA: Occupational Safety & Health TLV: Threshold Limit Value	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
BEI: Biological Exposure Limit	
Flam. Liq. 3: Flammable liquids – Category 3	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A	
Carc. 2: Carcinogenicity – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2	

CENERAL

Page 15/15