



Printing date 09/11/2019

Reviewed on 06/28/2019

#### 1 Identification

· Product identifier

· Trade name: 777C PEARL GREEN

· Article number: 777C

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: General Paint Co. S.A.L.

P.O. Box 7623

Beirut

**LEBANON** 

info@generalpaint.biz

- · Information department: Product Safety Department
- · Emergency telephone number: 1-800-535-5053 contract number (89244)

#### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)





Printing date 09/11/2019 Reviewed on 06/28/2019

Trade name: 777C PEARL GREEN

(Contd. of page 1)

#### · Hazard pictograms







GHS02 GHS07 GHS0

#### · Signal word Warning

#### · Hazard-determining components of labeling:

methyl acetate ethylbenzene

#### · Hazard statements

Flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

May cause drowsiness or dizziness.

May cause damage to the hearing organs through prolonged or repeated exposure.

#### · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)





Printing date 09/11/2019 Reviewed on 06/28/2019

Trade name: 777C PEARL GREEN

(Contd. of page 2)

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 3 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2
 Fire = 3
 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

_	Dangerous components:		
79-20-9	methyl acetate	>25- <i>≤</i> 50%	
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	>25- <i>≤</i> 50%	
64742-95-6	Solvent naphtha (petroleum), light arom.	>2.5-≤10%	
1330-20-7	xylene	>2.5-≤10%	
	ethyl 3-ethoxypropionate	>2.5-≤10%	
100-41-4	ethylbenzene	<i>≤</i> 2.5%	

#### 4 First-aid measures

- · Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: If symptoms persist consult doctor.

(Contd. on page 4)





Printing date 09/11/2019 Reviewed on 06/28/2019

Trade name: 777C PEARL GREEN

(Contd. of page 3)

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

PAC-1:		
79-20-9	methyl acetate	250 ppm
1330-20-7	xylene	130 ppm
763-69-9	ethyl 3-ethoxypropionate	1.6 ppm
100-41-4	ethylbenzene	33 ppm
107-98-2	1-methoxy-2-propanol	100 ppm
123-86-4	n-butyl acetate	5 ppm
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
7664-38-2	phosphoric acid	3 mg/m³

US





Printing date 09/11/2019 Reviewed on 06/28/2019

Trade name: 777C PEARL GREEN

70657-70-4	2-methoxypropyl acetate	(Contd. of page) 50 ppm
78-83-1		150 ppm
57-55-6	Propylene glycol	30 mg/m <sup>2</sup>
PAC-2:		
79-20-9	methyl acetate	1,700 ppm
1330-20-7	xylene	920* ppm
763-69-9	ethyl 3-ethoxypropionate	18 ppm
100-41-4	ethylbenzene	1100* ppm
107-98-2	1-methoxy-2-propanol	160 ppm
123-86-4	n-butyl acetate	200 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
7664-38-2	phosphoric acid	30 mg/m³
70657-70-4	2-methoxypropyl acetate	1,000 ppm
78-83-1	butanol	1,300 ppm
57-55-6	Propylene glycol	1,300 mg/m
PAC-3:		
79-20-9	methyl acetate	10000* ppm
1330-20-7	xylene	2500* ppm
763-69-9	ethyl 3-ethoxypropionate	110 ppm
100-41-4	ethylbenzene	1800* ppm
107-98-2	1-methoxy-2-propanol	660 ppm
123-86-4	n-butyl acetate	3000* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
7664-38-2	phosphoric acid	150 mg/m³
70657-70-4	2-methoxypropyl acetate	5,000 ppm
78-83-1	butanol	8000* ppm
57-55-6	Propylene glycol	7,900 mg/m <sup>2</sup>

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 6)





Printing date 09/11/2019 Reviewed on 06/28/2019

Trade name: 777C PEARL GREEN

(Contd. of page 5)

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

## 79-20-9 methyl acetate PEL Long-term value: 610 mg/m<sup>3</sup>, 200 ppm REL Short-term value: 760 mg/m³, 250 ppm Long-term value: 610 mg/m³, 200 ppm TLV Short-term value: 757 mg/m³, 250 ppm Long-term value: 606 mg/m³, 200 ppm 1330-20-7 xylene PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppm REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m<sup>3</sup>, 100 ppm TLV Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI 100-41-4 ethylbenzene PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppm REL Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm TLV Long-term value: 87 mg/m<sup>3</sup>, 20 ppm

#### · Ingredients with biological limit values:

#### 1330-20-7 xylene

BEI 1.5 g/g creatinine Medium: urine Time: end of shift

Parameter: Methylhippuric acids

(Contd. on page 7)





Printing date 09/11/2019 Reviewed on 06/28/2019

Trade name: 777C PEARL GREEN

(Contd. of page 6)

#### 100-41-4 ethylbenzene

BEI 0.7 g/g creatinine

Medium: urine

Time: end of shift at end of workweek

Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

Medium: end-exhaled air

Time: not critical

Parameter: Ethyl benzene (semi-quantitative)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

#### · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



#### Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 8)





Printing date 09/11/2019 Reviewed on 06/28/2019

Trade name: 777C PEARL GREEN

(Contd. of page 7)

· Eye protection:



Tightly sealed goggles

Information on basic physical and General Information	chemical properties
Appearance:	
Form:	Liquid
Color:	Green
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	57 °C (134.6 °F)
Flash point:	27 °C (80.6 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	455 °C (851 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive ai vapor mixtures are possible.
Explosion limits:	
Lower:	3.1 Vol %
Upper:	16 Vol %
Vapor pressure at 20 °C (68 °F):	220 hPa (165 mm Hg)
Density at 20 °C (68 °F):	1.13 g/cm³ (9.42985 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.

(Contd. on page 9)





Printing date 09/11/2019 Reviewed on 06/28/2019

Trade name: 777C PEARL GREEN

(Contd. of page 8)

· Viscosity:

**Dynamic:** Not determined. **Kinematic:** Not determined.

· Solvent content:

Organic solvents: 74.1 % Coating VOC content: 13.76 %

415.4 g/l / 3.47 lb/gal 155.5 g/l / 1.30 lb/gal

Solids content: 25.8 %

· Other information No further relevant information available.

## 10 Stability and reactivity

Material VOC content:

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

#### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

#### 64742-95-6 Solvent naphtha (petroleum), light arom.

 Oral
 LD50
 >6,800 mg/kg (rat)

 Dermal
 LD50
 >3,400 mg/kg (rab)

 Inhalative
 LC50/4 h
 >10.2 mg/l (rat)

- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

. Irritant

(Contd. on page 10)





Printing date 09/11/2019 Reviewed on 06/28/2019

Trade name: 777C PEARL GREEN

(Contd. of page 9)

· Carcinoge	nic categories		
•	rnational Agency for Research on Cancer)		
1330-20-7	xylene	3	
100-41-4	ethylbenzene	2B	
· NTP (National Toxicology Program)			
None of the ingredients is listed.			
· OSHA-Ca	(Occupational Safety & Health Administration)		
None of the ingredients is listed.			

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.





Printing date 09/11/2019 Reviewed on 06/28/2019

Trade name: 777C PEARL GREEN

(Contd. of page 10)

UN-Number DOT, ADR, IMDG, IATA	UN1263
UN proper shipping name DOT	Paint
ADR IMDG, IATA	1263 PAINT, ENVIRONMENTALLY HAZARDOUS PAINT
Transport hazard class(es)	
DOT	
RAMME FIGUR	
Class	3 Flammable liquids
Label	3
Class Label	3 Flammable liquids 3
Packing group	
DOT, ADR IMDG, IATA	 
Environmental hazards:	"
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
EMS Number:	F-E,S-E
Stowage Category	В
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L





Printing date 09/11/2019 Reviewed on 06/28/2019

Trade name: 777C PEARL GREEN

(Contd. of page 11)

(Conta. of page 1		
Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml		
5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml		
UN 1263 PAINT, 3, III, ENVIRONMENTALL HAZARDOUS		

## 15 Regulatory information

 $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  Sara

Section 313 (Specific toxic chemical listings):  1330-20-7 xylene  100-41-4 ethylbenzene  7664-38-2 phosphoric acid  TSCA (Toxic Substances Control Act):  79-20-9 methyl acetate  98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene  9004-36-8 cellulose acetate butyrate  1330-20-7 xylene	ACTIV ACTIV ACTIV
100-41-4 ethylbenzene 7664-38-2 phosphoric acid  TSCA (Toxic Substances Control Act): 79-20-9 methyl acetate 98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene 9004-36-8 cellulose acetate butyrate	ACTIV ACTIV
7664-38-2 phosphoric acid  TSCA (Toxic Substances Control Act):  79-20-9 methyl acetate  98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene  9004-36-8 cellulose acetate butyrate	ACTIV ACTIV
TSCA (Toxic Substances Control Act):  79-20-9 methyl acetate  98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene  9004-36-8 cellulose acetate butyrate	ACTIV ACTIV
79-20-9 methyl acetate 98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene 9004-36-8 cellulose acetate butyrate	ACTIV ACTIV
98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene 9004-36-8 cellulose acetate butyrate	ACTIV ACTIV
9004-36-8 cellulose acetate butyrate	ACTIV
·	
1330-20-7 xvlene	
	ACTI
763-69-9 ethyl 3-ethoxypropionate	ACTI
100-41-4 ethylbenzene	ACTI
107-98-2 1-methoxy-2-propanol	ACTI
123-86-4 n-butyl acetate	ACTI
108-65-6 2-methoxy-1-methylethyl acetate	ACTI
7664-38-2 phosphoric acid	ACTI
78-83-1 butanol	ACTI
57-55-6 Propylene glycol	ACT/\

(Contd. on page 13)





Reviewed on 06/28/2019 Printing date 09/11/2019

Trade name: 777C PEARL GREEN

(Contd. of page 12)

100-41-4 ethylbenzene

- · Proposition 65
- · Chemicals known to cause cancer:

100-41-4 ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

Carcinogenic categories

· EPA (Env	ronmental Protection Agency)	
1330-20-7	xylene	1
100-41-4	ethylbenzene	D

· TLV (Threshold Limit Value established by ACGIH)

•		•	,	
1330-20-7	xylene			A4
100-41-4	ethylbenzene			А3

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







GHS02 GHS07 GHS08

- · Signal word Warning
- · Hazard-determining components of labeling:

methyl acetate ethylbenzene

· Hazard statements

Flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

May cause drowsiness or dizziness.

May cause damage to the hearing organs through prolonged or repeated exposure.

(Contd. on page 14)





Printing date 09/11/2019 Reviewed on 06/28/2019

Trade name: 777C PEARL GREEN

(Contd. of page 13)

#### · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 09/11/2019 / -
- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 15)



Page 15/15

## Safety Data Sheet acc. to OSHA HCS

Printing date 09/11/2019 Reviewed on 06/28/2019

Trade name: 777C PEARL GREEN

(Contd. of page 14)

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3 Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2