Printing date 09/11/2019

Reviewed on 06/28/2019

## **1** Identification

- · Product identifier
- · Trade name: <u>778C PEARL BLUE</u>
- · Article number: 778C
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: General Paint Co. S.A.L. P.O. Box 7623 Beirut LEBANON info@generalpaint.biz
- Information department: Product Safety Department
   Emergency telephone number: 1-800-535-5053 contract number (89244)

### 2 Hazard(s) identification

· Classification of the substance or mixture GHS02 Flame Flam. Liq. 3 H226 Flammable liquid and vapor. GHS08 Health hazard H351 Suspected of causing cancer. Carc. 2 STOT RE2 H373 May cause damage to the hearing organs through prolonged or repeated exposure. GHS07 Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness. · Label elements · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 2) US



Page 1/15

Page 2/15

## Safety Data Sheet acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

### Trade name: 778C PEARL BLUE

(Contd. of page 1) · Hazard pictograms GHS02 GHS07 GHS08 · Signal word Warning Hazard-determining components of labeling: methyl acetate ethylbenzene · Hazard statements Flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. May cause drowsiness or dizziness. May cause damage to the hearing organs through prolonged or repeated exposure. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. (Contd. on page 3)



*Printing date 09/11/2019* 

Reviewed on 06/28/2019

## Trade name: 778C PEARL BLUE

Classification system:
 NFPA ratings (scale 0 - 4)



## · HMIS-ratings (scale 0 - 4)



## · Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

## 3 Composition/information on ingredients

## · Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
	methyl acetate	>25- <i>≤</i> 50%	
	4-chloro-alpha,alpha,alpha-trifluorotoluene	>25- <i>≤</i> 50%	
64742-95-6	Solvent naphtha (petroleum), light arom.	>2.5- <i>≤</i> 10%	
1330-20-7	xylene	>2.5- <i>≤</i> 10%	
763-69-9	ethyl 3-ethoxypropionate	<i>≤</i> 2.5%	
100-41-4	ethylbenzene	<i>≤</i> 2.5%	

## 4 First-aid measures

## · Description of first aid measures

General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • After swallowing: If symptoms persist consult doctor.

(Contd. on page 4)

US

## Page 3/15



(Contd. of page 2)

Printing date 09/11/2019

Reviewed on 06/28/2019

(Contd. of page 3)

## Trade name: 778C PEARL BLUE

- · Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

## 6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

## Protective Action Criteria for Chemicals

· PAC-1:		
79-2	0-9 methyl acetate	250 ppm
1330-2	0-7 xylene	130 ppm
763-6	9-9 ethyl 3-ethoxypropionate	1.6 ppm
100-4	1-4 ethylbenzene	33 ppm
107-9	8-2 1-methoxy-2-propanol	100 ppm
123-8	6-4 n-butyl acetate	5 ppm
108-6	5-6 2-methoxy-1-methylethyl acetate	50 ppm
7664-3	8-2 phosphoric acid	3 mg/m <sup>3</sup>
		(Contd. on page



Printing date 09/11/2019

Reviewed on 06/28/2019

Page 5/15

## Trade name: 778C PEARL BLUE

70057 70 4		(Contd. of page
	2-methoxypropyl acetate	50 ppm
	butanol	150 ppm
57-55-6	Propylene glycol	30 mg/m
PAC-2:		
79-20-9	methyl acetate	1,700 ppm
1330-20-7	xylene	920* ppm
763-69-9	ethyl 3-ethoxypropionate	18 ppm
100-41-4	ethylbenzene	1100* ppm
107-98-2	1-methoxy-2-propanol	160 ppm
123-86-4	n-butyl acetate	200 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
7664-38-2	phosphoric acid	30 mg/m <sup>3</sup>
70657-70-4	2-methoxypropyl acetate	1,000 ppm
78-83-1	butanol	1,300 ppm
57-55-6	Propylene glycol	1,300 mg/m
PAC-3:		
79-20-9	methyl acetate	10000* ppm
1330-20-7	xylene	2500* ppm
763-69-9	ethyl 3-ethoxypropionate	110 ppm
100-41-4	ethylbenzene	1800* ppm
107-98-2	1-methoxy-2-propanol	660 ppm
123-86-4	n-butyl acetate	3000* ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
7664-38-2	phosphoric acid	150 mg/m <sup>3</sup>
70657-70-4	2-methoxypropyl acetate	5,000 ppm
78-83-1	butanol	8000* ppm
57-55-6	Propylene glycol	7,900 mg/m

## 7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

(Contd. on page 6)



Printing date 09/11/2019

## Reviewed on 06/28/2019

Page 6/15

(Contd. of page 5)

## Trade name: 778C PEARL BLUE

Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles: No special requirements.

· Information about storage in one common storage facility: Not required.

- Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 3
- · Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

## 79-20-9 methyl acetate PEL Long-term value: 610 mg/m<sup>3</sup>, 200 ppm REL Short-term value: 760 mg/m<sup>3</sup>, 250 ppm Long-term value: 610 mg/m<sup>3</sup>, 200 ppm TLV Short-term value: 757 mg/m<sup>3</sup>, 250 ppm Long-term value: 606 mg/m<sup>3</sup>, 200 ppm 1330-20-7 xylene PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppm REL Short-term value: 655 mg/m<sup>3</sup>, 150 ppm Long-term value: 435 mg/m<sup>3</sup>, 100 ppm TLV Short-term value: 651 mg/m<sup>3</sup>, 150 ppm Long-term value: 434 mg/m<sup>3</sup>, 100 ppm BEI 100-41-4 ethylbenzene PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppm REL Short-term value: 545 mg/m<sup>3</sup>, 125 ppm Long-term value: 435 mg/m<sup>3</sup>, 100 ppm TLV Long-term value: 87 mg/m<sup>3</sup>, 20 ppm BEI · Ingredients with biological limit values: 1330-20-7 xylene BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids (Contd. on page 7)



Page 7/15

(Contd. of page 6)

## Safety Data Sheet acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

## Trade name: 778C PEARL BLUE

## 100-41-4 ethylbenzene

BEI 0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

· Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin.
- · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 8)

Printing date 09/11/2019

Reviewed on 06/28/2019

## Trade name: 778C PEARL BLUE

· Eye protection:

Tightly sealed goggles

## 9 Physical and chemical properties

General Information Appearance:	
Form:	Liquid
Color:	Blue
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	57 °C (134.6 °F)
Flash point:	25 °C (77 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	455 °C (851 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air vapor mixtures are possible.
Explosion limits:	
Lower:	3.1 Vol %
Upper:	16 Vol %
Vapor pressure at 20 °C (68 °F):	220 hPa (165 mm Hg)
Density at 20 °C (68 °F):	1.13 g/cm³ (9.42985 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	er): Not determined.



(Contd. of page 7)



*Printing date 09/11/2019* 

Reviewed on 06/28/2019

## Trade name: 778C PEARL BLUE

	()	Contd. of page 8
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	73.4 %	
Coating VOC content:	13.75 %	
Ū	416.3 g/l / 3.47 lb/gal	
Material VOC content:	155.3 g/l / 1.30 lb/gal	
Solids content:	26.5 %	
Other information	No further relevant information available.	

## 10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classified	cation:
---	---------

64742-95-6 Solvent naphtha (petroleum), light arom					
Oral	LD50	>6,800 mg/kg (rat)			
Dermal	LD50	>6,800 mg/kg (rat) >3,400 mg/kg (rab)			
Inhalative	LC50/4 h	>10.2 mg/l (rat)			

## · Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

(Contd. on page 10)



Page 9/15

US

Page 10/15

(Contd. of page 9)

3

2B

## Safety Data Sheet acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

### Trade name: 778C PEARL BLUE

#### · Carcinogenic categories

· IARC (International Agency for Research on Cancer)

1330-20-7 xylene

100-41-4 ethylbenzene

## · NTP (National Toxicology Program)

None of the ingredients is listed.

## · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

#### · Toxicity

- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:

## · General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

(Contd. on page 11)



Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 778C PEARL BLUE

(Contd. of page 10)

UN-Number DOT, ADR, IMDG, IATA	UN1263
UN proper shipping name DOT ADR IMDG, IATA	Paint 1263 PAINT, ENVIRONMENTALLY HAZARDOUS PAINT
Transport hazard class(es)	
DOT	
Class	3 Flammable liquids
Label	3
Class	2 Elammable liquida
Class Label	3 Flammable liquids 3
Class	8 Corrosive substances
Label	3
Packing group DOT, ADR, IMDG, IATA	III
Environmental hazards: Marine pollutant:	Νο
Special precautions for user EMS Number: Stowage Category	Warning: Flammable liquids F-E,S-E A
Transport in bulk according to Anne MARPOL73/78 and the IBC Code	ex II of Not applicable.



Page 11/15

Page 12/15

# Safety Data Sheet acc. to OSHA HCS

Printing date 09/11/2019

Reviewed on 06/28/2019

Trade name: 778C PEARL BLUE

	(Contd. of page
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
ADR	
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT, 3, III, ENVIRONMENTALL HAZARDOUS

## 15 Regulatory information

 $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  Sara

None of the	e ingredients is listed.	
Section 31	13 (Specific toxic chemical listings):	
1330-20-7	xylene	
100-41-4	ethylbenzene	
7664-38-2	phosphoric acid	
TSCA (To	xic Substances Control Act):	
79-20-9	methyl acetate	ACTIV
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	ACTIV
9004-36-8	cellulose acetate butyrate	ACTIV
1330-20-7	xylene	ACTIV
763-69-9	ethyl 3-ethoxypropionate	ACTIV
100-41-4	ethylbenzene	ACTIV
107-98-2	1-methoxy-2-propanol	ACTIV
123-86-4	n-butyl acetate	ACTIV
108-65-6	2-methoxy-1-methylethyl acetate	ACTIV
7664-38-2	phosphoric acid	ACTIV



Page 13/15

# Safety Data Sheet acc. to OSHA HCS

Printing date 09/11/2019

GENERAL

Reviewed on 06/28/2019

## Trade name: 778C PEARL BLUE

		ontd. of page 1
	butanol	ACTIVE
57-55-6	Propylene glycol	ACTIVE
·Hazardou	s Air Pollutants	
1330-20-7	xylene	
100-41-4	ethylbenzene	
· Propositio		
	s known to cause cancer:	
100-41-4	ethylbenzene	
· Chemicals	s known to cause reproductive toxicity for females:	
None of th	e ingredients is listed.	
· Chemicals	s known to cause reproductive toxicity for males:	
None of th	e ingredients is listed.	
· Chemicals	s known to cause developmental toxicity:	
None of th	e ingredients is listed.	
· Carcinoge	enic categories	
· EPA (Envi	ironmental Protection Agency)	
1330-20-7	•	1
100-41-4	ethylbenzene	L
· TLV (Thre	shold Limit Value established by ACGIH)	
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A
· NIOSH-Ca	(National Institute for Occupational Safety and Health)	
None of th	e ingredients is listed.	
<ul> <li>GHS label</li> <li>The produce</li> <li>Hazard pice</li> </ul>	ct is classified and labeled according to the Globally Harmonized System (GHS)	).
GHS02	GHS07 GHS08	
· Signal wo	rd Warning	
· Hazard-de	termining components of labeling:	

- methyl acetate ethylbenzene
- Hazard statements Flammable liquid and vapor. Causes skin irritation.

(Contd. on page 14)

US

Page 14/15

## Safety Data Sheet acc. to OSHA HCS

*Printing date 09/11/2019* 

## Reviewed on 06/28/2019

### Trade name: 778C PEARL BLUE

(Contd. of page 13) Causes serious eye irritation. Suspected of causing cancer. May cause drowsiness or dizziness. May cause damage to the hearing organs through prolonged or repeated exposure. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 09/11/2019 / -
- · Abbreviations and acronyms:
- ICAO: International Civil Aviation Organisation RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

ADR: Accord europeen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 15)

CENERAL

Printing date 09/11/2019

## Reviewed on 06/28/2019

## Trade name: 778C PEARL BLUE

<ul> <li>IMDG: International Maritime Code for Dangerous Goods</li> <li>DOT: US Department of Transportation</li> <li>IATA: International Air Transport Association</li> <li>ACGIH: American Conference of Governmental Industrial Hygienists</li> <li>EINECS: European Inventory of Existing Commercial Chemical Substances</li> <li>ELINCS: European List of Notified Chemical Substances</li> <li>CAS: Chemical Abstracts Service (division of the American Chemical Society)</li> <li>NFPA: National Fire Protection Association (USA)</li> <li>HMIS: Hazardous Materials Identification System (USA)</li> <li>VOC: Volatile Organic Compounds (USA, EU)</li> <li>LC50: Lethal concentration, 50 percent</li> <li>LD50: Lethal concentration, 50 percent</li> <li>VD57: Very Persistent, Bioaccumulative and Toxic</li> <li>vPvB: very Persistent and very Bioaccumulative</li> <li>NIOSH: National Institute for Occupational Safety</li> <li>OSHA: Occupational Safety &amp; Health</li> <li>TLV: Threshold Limit Value</li> <li>PEL: Permissible Exposure Limit</li> <li>REL: Recommended Exposure Limit</li> <li>REL: Recommended Exposure Limit</li> <li>Flam. Liq. 3: Flammable liquids – Category 3</li> <li>Skin Irrit. 2: Skin corrosion/irritation – Category 2</li> <li>Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A</li> <li>Carc. 2: Carcinogenicity – Category 2</li> <li>STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2</li> </ul>	(Contd. of page 14)
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2	115



Page 15/15