



Printing date 09/11/2019 Reviewed on 06/28/2019

### 1 Identification

· Product identifier

· Trade name: 799C METALLIC BASE SUPER FINE

· Article number: 799C

· Details of the supplier of the safety data sheet

Manufacturer/Supplier: General Paint Co. S.A.L.

P.O. Box 7623

Beirut LEBANON

info@generalpaint.biz

· Information department: Product Safety Department

· Emergency telephone number: 1-800-535-5053 contract number (89244)

# 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.

Water-react. 1 H260 In contact with water releases flammable gases, which may ignite

spontaneously.



#### GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

STOT RE 1 H372-H373 Causes damage to the central nervous system through prolonged or

repeated exposure. May cause damage to the hearing organs through

prolonged or repeated exposure.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)





Printing date 09/11/2019 Reviewed on 06/28/2019

Trade name: 799C METALLIC BASE SUPER FINE

(Contd. of page 1)

### · Hazard pictograms







GHS02 GHS07 GHS0

#### · Signal word Danger

### · Hazard-determining components of labeling:

methyl acetate

ethylbenzene

Stoddard solvent

#### · Hazard statements

Flammable liquid and vapor.

In contact with water releases flammable gases, which may ignite spontaneously.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

May cause drowsiness or dizziness.

Causes damage to the central nervous system through prolonged or repeated exposure. May cause damage to the hearing organs through prolonged or repeated exposure.

#### · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not allow contact with water.

Handle under inert gas. Protect from moisture.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

(Contd. on page 3)





Printing date 09/11/2019 Reviewed on 06/28/2019

#### Trade name: 799C METALLIC BASE SUPER FINE

(Contd. of page 2)

Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, sand, extinguishing powder.

Store in a dry place. Store in a closed container.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 3Reactivity = 2

The substance demonstrates unusual reactivity with water.

· HMIS-ratings (scale 0 - 4)



Health = 2Fire = 3Reactivity = 2

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

# 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous	components:	
79-20-9	methyl acetate	>25- <i>≤</i> 50%
	4-chloro-alpha,alpha,alpha-trifluorotoluene	>25- <i>≤</i> 50%
	Solvent naphtha (petroleum), light arom.	>2.5- <i>≤</i> 10%
1330-20-7	1 5	>2.5-≤10%
	ethyl 3-ethoxypropionate	>2.5-≤10%
	aluminium powder (pyrophoric)	>2.5- <i>≤</i> 10%
	Stoddard solvent	≤2.5%
100-41-4	ethylbenzene	≤2.5%



Page 4/15

# Safety Data Sheet acc. to OSHA HCS

Printing date 09/11/2019 Reviewed on 06/28/2019

Trade name: 799C METALLIC BASE SUPER FINE

(Contd. of page 3)

# 4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Extinguishing powder. Do not use water.

CO2. Do not use water.

Sand. Do not use water.

Special powder for metal fires. Do not use water.

CO2, sand, extinguishing powder. Do not use water.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · **Protective equipment:** Mouth respiratory protective device.

## 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

(Contd. on page 5)





Printing date 09/11/2019 Reviewed on 06/28/2019

Trade name: 799C METALLIC BASE SUPER FINE

(Contd. of page 4)

#### · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

PAC-1:		
79-20-9	methyl acetate	250 ppn
1330-20-7	xylene	130 ppn
763-69-9	ethyl 3-ethoxypropionate	1.6 ppm
100-41-4	ethylbenzene	33 ppm
107-98-2	1-methoxy-2-propanol	100 ppn
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
7664-38-2	phosphoric acid	3 mg/m <sup>-</sup>
70657-70-4	2-methoxypropyl acetate	50 ppm
PAC-2:		
79-20-9	methyl acetate	1,700 ppn
1330-20-7	xylene	920* ppm
763-69-9	ethyl 3-ethoxypropionate	18 ppm
100-41-4	ethylbenzene	1100* ppr
107-98-2	1-methoxy-2-propanol	160 ppm
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppn
7664-38-2	phosphoric acid	30 mg/m³
70657-70-4	2-methoxypropyl acetate	1,000 ppn
PAC-3:		·
79-20-9	methyl acetate	10000* ppr
1330-20-7	xylene	2500* ppm
763-69-9	ethyl 3-ethoxypropionate	110 ppm
100-41-4	ethylbenzene	1800* ppm
107-98-2	1-methoxy-2-propanol	660 ppm
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
7664-38-2	phosphoric acid	150 mg/m³
70657-70-4	2-methoxypropyl acetate	5,000 ppm

# 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

(Contd. on page 6)





Printing date 09/11/2019 Reviewed on 06/28/2019

Trade name: 799C METALLIC BASE SUPER FINE

(Contd. of page 5)

Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 4.3
- · Specific end use(s) No further relevant information available.

# 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

79-20	0-9 methyl acetate	
PEL	Long-term value: 610 mg/m³, 200 ppm	
REL	Short-term value: 760 mg/m³, 250 ppm Long-term value: 610 mg/m³, 200 ppm	
TLV	Short-term value: 757 mg/m³, 250 ppm Long-term value: 606 mg/m³, 200 ppm	
1330	-20-7 xylene	
PEL	Long-term value: 435 mg/m³, 100 ppm	
REL	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm	
TLV	Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI	
8052	8052-41-3 Stoddard solvent	
PEL	Long-term value: 2900 mg/m³, 500 ppm	
REL	Long-term value: 350 mg/m³ Ceiling limit value: 1800* mg/m³ *15-min	

(Contd. on page 7)





Printing date 09/11/2019 Reviewed on 06/28/2019

Trade name: 799C METALLIC BASE SUPER FINE

	(Contd. of page 6)
TLV	Long-term value: 525 mg/m³, 100 ppm
100-	41-4 ethylbenzene
PEL	Long-term value: 435 mg/m³, 100 ppm
REL	Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm
TLV	Long-term value: 87 mg/m³, 20 ppm BEI
· Ingre	edients with biological limit values:
1330	20-7 xylene
	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
100-	41-4 ethylbenzene
	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek

Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

Medium: end-exhaled air

Time: not critical

Parameter: Ethyl benzene (semi-quantitative)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 8)





Printing date 09/11/2019 Reviewed on 06/28/2019

Trade name: 799C METALLIC BASE SUPER FINE

(Contd. of page 7)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

# 9 Physical and chemical properties

· Information on basic physical and	chemical properties
· General Information	, ,
· Appearance:	
Form:	Liquid
Color:	Grey
Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 57°C (134.6°F)
· Flash point:	24 °C (75.2 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	455 °C (851 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
	(Contd. on page 9)





Printing date 09/11/2019 Reviewed on 06/28/2019

Trade name: 799C METALLIC BASE SUPER FINE

	(Con	td. of page
Explosion limits:		
Lower:	3.1 Vol %	
Upper:	16 Vol %	
Vapor pressure at 20 °C (68 °F):	220 hPa (165 mm Hg)	
Density at 20 °C (68 °F):	1.119 g/cm³ (9.33806 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wat	er): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	75.0 %	
Coating VOC content:	14.18 %	
_	419.1 g/l / 3.50 lb/gal	
Material VOC content:	158.7 g/l / 1.32 lb/gal	
Solids content:	23.6 %	
Other information	No further relevant information available.	

#### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions Contact with water releases flammable gases.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

110





Printing date 09/11/2019 Reviewed on 06/28/2019

Trade name: 799C METALLIC BASE SUPER FINE

(Contd. of page 9)

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

### 64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6,800 mg/kg (rat)
Dermal		>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· Carcinogenic categories

· IARC (Inte	rnational Agency for Research on Cancer)	
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

#### · NTP (National Toxicology Program)

None of the ingredients is listed.

# · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 11)





Printing date 09/11/2019 Reviewed on 06/28/2019

Trade name: 799C METALLIC BASE SUPER FINE

(Contd. of page 10)

- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

# 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

· UN-Number

· DOT, ADR, IMDG, IATA UN1263

· UN proper shipping name

· DOT

Paint

· ADR 1263 PAINT, ENVIRONMENTALLY HAZARDOUS

· IMDG, IATA **PAINT** 

- · Transport hazard class(es)
- · DOT



· Class 3 Flammable liquids

· Label

· ADR, IMDG, IATA



· Class 3 Flammable liquids

· Label

· Packing group · DOT, ADR, IMDG, IATA III

(Contd. on page 12)





Printing date 09/11/2019 Reviewed on 06/28/2019

Trade name: 799C METALLIC BASE SUPER FINE

	(Contd. of page 11
Environmental hazards: Marine pollutant:	No
Special precautions for user EMS Number: Stowage Category	Warning: Flammable liquids F-E, <u>S-E</u> A
Transport in bulk according to Annex I MARPOL73/78 and the IBC Code	<b>II of</b> Not applicable.
Transport/Additional information:	
DOT Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
ADR Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT, 3, III, ENVIRONMENTALL HAZARDOUS

# 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara		
· Section 35	5 (extremely hazardous substances):	
None of the	e ingredients is listed.	
· Section 31	3 (Specific toxic chemical listings):	
1330-20-7	xylene	
7429-90-5	aluminium powder (pyrophoric)	
	ethylbenzene	
7664-38-2	phosphoric acid	
· TSCA (Tox	ric Substances Control Act):	
79-20-9	methyl acetate	ACTIVE
98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	ACTIVE
	(Contd.	on page 13)





Printing date 09/11/2019 Reviewed on 06/28/2019

Trade name: 799C METALLIC BASE SUPER FINE

9004-36-8	cellulose acetate butyrate	ACTI
1330-20-7		ACTIV
763-69-9	ethyl 3-ethoxypropionate	ACTIV
7429-90-5	aluminium powder (pyrophoric)	ACTIV
100-41-4	ethylbenzene	ACTI
107-98-2	1-methoxy-2-propanol	ACTI
108-65-6	2-methoxy-1-methylethyl acetate	ACTI
7664-38-2	phosphoric acid	ACTI <sup>1</sup>
· Hazardou	s Air Pollutants	
1330-20-7	xylene	
100-41-4	ethylbenzene	
· Propositi	on 65	
	s known to cause cancer:	
100-41-4	ethylbenzene	
· Chemical	s known to cause reproductive toxicity for females:	
None of th	e ingredients is listed.	
· Chemical	s known to cause reproductive toxicity for males:	
None of th	e ingredients is listed.	
Chemical	s known to cause developmental toxicity:	
None of th	e ingredients is listed.	
Carcinog	enic categories	
	ironmental Protection Agency)	
1330-20-7	xylene	
100-41-4	ethylbenzene	
· TLV (Thre	shold Limit Value established by ACGIH)	
1330-20-7	xylene	
7429-90-5	aluminium powder (pyrophoric)	
100-41-4	ethylbenzene	,
. NIOSH-C	a (National Institute for Occupational Safety and Healt	h)

GHS label elements
The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 14)





Printing date 09/11/2019 Reviewed on 06/28/2019

Trade name: 799C METALLIC BASE SUPER FINE

(Contd. of page 13)

### · Hazard pictograms







GHS02 GHS07 GHS08

#### · Signal word Danger

#### · Hazard-determining components of labeling:

methyl acetate

ethylbenzene

Stoddard solvent

#### · Hazard statements

Flammable liquid and vapor.

In contact with water releases flammable gases, which may ignite spontaneously.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

May cause drowsiness or dizziness.

Causes damage to the central nervous system through prolonged or repeated exposure. May cause damage to the hearing organs through prolonged or repeated exposure.

#### · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not allow contact with water.

Handle under inert gas. Protect from moisture.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

(Contd. on page 15)





Reviewed on 06/28/2019 Printing date 09/11/2019

Trade name: 799C METALLIC BASE SUPER FINE

(Contd. of page 14)

Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, sand, extinguishing powder.

Store in a dry place. Store in a closed container.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: Product safety department
- · Contact: N/A
- · Date of preparation / last revision 09/11/2019 / -
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids - Category 3

Water-react. 1: Substances and mixtures which in contact with water emit flammable gases - Category 1

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1