



G77Y – Polyester Putty Beige

Description:

This great metal filler is a multi-purpose putty with an extremely smooth application. It can be applied vertically without running and exhibits high resistance to almost all solvents.

Suitable Substrates:

- Iron, steel plate, glass fiber reinforced plastic
- Original paints or aged topcoat finishes

Surface Preparation:

- Clean well the surface to be treated with 8241 Genclean. Make sure it is dry and free from
- Silicone, wax, grease and any extraneous material.
- On basecoats or enamel top coats, sand and clean the surface before applying the filler.



1 – 3% General hardener
Potlife 3 - 5 min at 20°C



Application with putty knife



< 30 min at 20°C



4 – 5 min at 1 m.



Initial Sanding with P60 – P120 roughing-out
Final Sanding with P180 – P220 finishing



G77Y – Polyester Putty Beige

Composition: Unsaturated polyester resin and mineral charges

Specific weight: 1.88 ± 0.1

Available Colors: Beige, Grey

VOC (2004/42/EC): 2004/42/IIB (b) (250)250. The EU limit value for this product (product category IIB.b) in ready to use form is max 250g/ltr. The VOC content of this product in ready for use form is max. 250 g/l.

SDS: Refer to the safety data sheet

Product Data Sheet